

SAFETY DATA SHEET

Bio+ Solid Flatware Presoak

SECTION 1: PRODUCT & COMPANY IDENTIFICATION

DATE: 02/05/2015 / Supersedes Revision: n/a

Manufacturer:

Native Green
2110 East Walton Blvd.
Auburn Hills, MI 48326
Phone: (888) 456-6444
Website: www.nativegreen.com

EMERGENCY CONTACT: Chemtrec, Reference CCN203605

Phone: (800) 424-9300 (collect calls accepted) / International: (703) 527-3887

Product Name: Bio+ Solid Flatware Presoak

ID Code: 547-0208

Product Category: Alkaline Detergent

SECTION 2: HAZARD(S) IDENTIFICATION

Acute Toxicity: Oral, Category 4

Skin Corrosion/Irritation, Category 1C

Serious Eye Damage/Eye Irritation, Category 2A



GHS Signal Word: DANGER

GHS Hazard Phrases:

H302 - Harmful if swallowed.

H314 - Causes severe skin burns and eye damage.

GHS Precaution Phrases:

P264 - Wash hands thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product.

P260 - Do not breathe dust/fume/gas/mist/vapours/spray.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

GHS Response Phrases:

P301+312 - IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

P330 - Rinse mouth.

P303+361+353 - IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.

P363 - Wash contaminated clothing before reuse.

P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison control center or physician for treatment advice. Have product container or label with you when calling poison control center or physician.

P301+330+331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P310 - Immediately call a POISON CENTER/doctor.

GHS Storage and Disposal Phrases:

P405 - Store locked up

P501 - Unused product is not a RCRA Hazardous waste. However, contaminated product and wastes may be RCRA hazardous. Users are advised to determine the appropriate disposal method based on local, state and federal regulations and comply with those regulations.

Hazard Rating System:

HMIS

Health: 2

Flammability: 0

Physical: 1

PPE: B

NFPA

Health: 2

Flammability: 0

Instability: 1

Special Hazard:

Potential Health Effects (Acute and Chronic): Adverse reproductive effects have been reported in animals. Chronic: None.

Inhalation: No hazard expected in normal industrial use.

Skin Contact: Causes skin burns.

Eye Contact: Causes eye burns.

Ingestion: Harmful if swallowed. Causes burns. No hazard expected in normal industrial use.

SAFETY DATA SHEET

Bio+ Solid Flatware Presoak

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

CAS #	Hazardous Components (Chemical Name)	Concentration
6834-92-0	Silicic acid (H ₂ SiO ₃), Disodium salt	<=47.0 %

SECTION 4: FIRST-AID MEASURES

Emergency and First Aid Procedures:

In Case of Inhalation: If breathed in, move person into fresh air. If breathing is difficult, give oxygen. Get medical aid if cough or other symptoms appear.

In Case of Skin Contact: Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. Consult a physician..

In Case of Eye Contact: Flush eye with water for 15 minutes. Get medical attention.

In Case of Ingestion: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

Signs and Symptoms of Exposure: Burning sensation, Breathing dusts from the use of this product may be harmful. Wheezing, Laryngitis, Shortness of breath.

Note to Physician: Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area. None known.

SECTION 5: FIRE-FIGHTING MEASURES

Flash Point: ~ 200.00 F Method Used: Estimate

Explosive Limits: LEL: UEL:

Autoignition Pt:

Suitable Extinguishing Media: Material is non-combustible. Use extinguishing agent suitable for type of surrounding fire.

Fire Fighting Instructions: Wear self contained breathing apparatus for fire fighting if necessary. Further information. The product itself does not burn. As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear. Material will not burn.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Steps To Be Taken In Case Material Is Released Or Spilled: Personal precautions. Use personal protective equipment. Avoid dust formation. Ensure adequate ventilation. Environmental precautions. Do not let product enter drains.

Use proper personal protective equipment as indicated in Section 8. Spills/Leaks: Absorb spill with inert material (e.g. vermiculite, sand or earth), then place in suitable container. Vacuum or sweep up material and place into a suitable disposal container. Avoid generating dusty conditions. Do not let this chemical enter the environment.

SECTION 7: HANDLING AND STORAGE

Precautions To Be Taken in Handling: Avoid contact with eyes, skin, and clothing. Avoid ingestion and inhalation. Do not get in eyes, on skin, or on clothing. Do not ingest or inhale.

Precautions To Be Taken in Storing: Keep container tightly closed in a dry and well-ventilated place. Hygroscopic.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

CAS #	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
6834-92-0	Silicic acid (H ₂ SiO ₃), Disodium salt			

Respiratory Equipment (Specify Type): Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU). Respirator protection is not normally required. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements or European Standard EN 149 must be followed whenever workplace conditions warrant respirator use.

Eye Protection: Face shield and safety glasses. Eye protection is not normally required. Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.

Protective Gloves: Handle with gloves. Protective garments not normally required. Wear appropriate protective gloves to prevent skin exposure.

Other Protective Clothing: Choose body protection according to the amount and concentration of the dangerous substance at the work place. Protective garments not normally required. Wear appropriate protective clothing to prevent skin exposure.

SAFETY DATA SHEET

Bio+ Solid Flatware Presoak

Engineering Controls (Ventilation etc.): There are no special ventilation requirements.

Work/Hygienic/Maintenance Practices: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Physical States: Gas Liquid Solid

Appearance and Odor: Green solid block

mild odor.

Melting Point:

Boiling Point:

Autoignition Pt:

Flash Pt:

Explosive Limits: LEL: UEL:

Specific Gravity (Water = 1): ~ 1.000

Density: >=1.5 G/CC

Vapor Pressure (vs. Air or mm Hg):

Vapor Density (vs. Air=1):

Evaporation Rate:

Solubility in Water: 100% at 72.0 F

Solubility Notes: Slightly soluble in water.

Viscosity:

pH: > 11.5

Percent Volatile:

SECTION 10: STABILITY AND REACTIVITY

Stability: Unstable Stable

Conditions To Avoid - Instability: Strong oxidizing agents. Strong acids.

Incompatibility – Materials To Avoid: Strong bases, Strong acids.

Hazardous Decomposition Or Byproducts: formed under fire conditions. Sodium oxides, silicon oxides. None. Carbon monoxide, Carbon dioxide.

Possibility of Hazardous Reactions: Will occur Will not occur

Conditions To Avoid -Hazardous Reactions:

SECTION 11: TOXICOLOGICAL INFORMATION

Toxicological Information: Epidemiology: No data available. Teratogenicity: No data available. Reproductive Effects: Mutagenicity: Neurotoxicity: Other Studies: No information found. Teratogenicity: No information available.

Irritation or Corrosion: Skin - rabbit - Severe skin irritation - -24 h. Acute demal toxicity: LD50 rabbit Dose > 2,000 mg/kg
Skin irritation: Rabbit Non irritant Eye irritation: Rabbit minimal irritant. .The acute oral toxicity of this product has not been tested. When sodium silicates were tested on a 100% solids basis, their single dose acute oral LD50 in rats ranged from 1500 mg/kg to 3200 mg/kg. Acute lethality resulted from nonspecific causes.

Carcinogenicity/Other Information: Carcinogenicity. IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC. ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP. OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA. CAS# 7732-18-5: Not listed by ACGIH, IARC, NTP, or CA Prop 65. CAS# 68-04-2: Not listed by ACGIH, IARC, NTP, or CA Prop 65. CAS# 497-19-8: Not listed by ACGIH, IARC, NTP, or CA Prop 65.

CAS #	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
6834-92-0	Silicic acid (H ₂ SiO ₃), Disodium salt	n.a.	n.a.	n.a.	n.a.

SECTION 12: ECOLOGICAL INFORMATION

General Ecological Information: Environmental: Not regulated under U.S. Department of Transportation regulations (29 CFR) Physical: No information available. Other: Do not empty into drains.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Method: Product. Observe all federal, state, and local environmental regulations. Contact a licensed professional waste disposal service to dispose of this material. Contaminated packaging. Dispose of as unused product. Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR Parts 261. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification. RCRA P-Series: None listed. RCRA U-Series: None listed.

SAFETY DATA SHEET

Bio+ Solid Flatware Presoak

SECTION 14: TRANSPORTATION INFORMATION (DOT/UN CLASSIFICATION)

LAND TRANSPORT (US DOT):

DOT Proper Shipping Name: Not regulated as a hazardous material.

DOT Hazard Class:

UN/NA Number:

Packing Group:

TDG Shipping Name:

SECTION 15: REGULATORY INFORMATION

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
6834-92-0	Silicic acid (H ₂ SiO ₃), Disodium salt	No	No	No

CAS #	Hazardous Components (Chemical Name)	Other US EPA or State Lists
6834-92-0	Silicic acid (H ₂ SiO ₃), Disodium salt	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No

SECTION 16: OTHER INFORMATION

Revision Date: 02/05/2015

Preparer Name: Regulatory Affairs

Additional Information About This Product:

Company Policy or Disclaimer: The information contained in this Safety Data Sheet is provided pursuant to current OSHA regulations to convey information concerning the hazardous nature of the named product. The information supplied was compiled from the most reliable sources available at the time of preparation and in light of the most reasonable foreseeable exposure situations expected from the intended use of this product. The material(s) may present greater or lesser hazard exposure under other circumstances that are beyond the control of the manufacturer. Therefore it is imperative that all directions and warnings on the product label be read and closely followed.