

=====

MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.

=====

PRODUCT NUMBER: 925947

IDENTITY: BOUNCE ELEC SEALER

Next Revision Date: November 30, 2019

Section I

Manufacturer's Name: MINERALS TECHNOLOGY***

Telephone Numbers:

Address: 4721 PASO DEL PUMA NE

Emergency:

800/255-3924

ALBUQUERQUE

EMERGENCY PHONE:

State: NM Zip Code: 871113076

505 238-0852

HMIS CODES: REACTIVITY: 0 FLAMMABILITY: 4 HEALTH: 3 PERSONAL PROTECT: A

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the ingredients contained in this product are listed on the TSCA inventory.)

=====

Name	Cas No.	OSHA PEL	ACGIH TLV	OTHER LIM	%
ACETONE	67-64-1	1000 PPM	750 PPM	N/A	-----
HEXANE	* 110-54-3	50 PPM	50 PPM	N/A	-----
PROPANE/N-BUTANE	68476-86-8	1000 PPM	600 PPM	N/A	-----
TOLUENE	*+ 108-88-3	100 PPM	50 PPM	N/A	-----
XYLENE (XYLOL)	* 1330-20-7	100 PPM	100 PPM	N/A	-----

Comment:

THIS PRODUCT CONTAINS THE TOXIC CHEMICALS MARKED WITH AN * SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF THE EMERGENCY PLANNING AND COMMUNITY RIGHT-TO-KNOW ACT OF 1986 AND OF 40CFR372.

THIS PRODUCT CONTAINS CHEMICAL(S) MARKED WITH A + KNOWN TO THE STATE OF CALIFORNIA TO CAUSE BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS

=====

Boiling Point:	N/A	Specific Gravity (water=1)	0.77
Vapor Pressure(mm Hg)	<75PSI	Melting Point:	N/A
Vapor Density(AIR=1)	>1	Evaporation Rate:	>1
Solubility in Water:	0%	(Butyl Acetate=1)	
Appearance and Odor:	CLEAR COATING, MILD ODOR		

Section IV: FIRE AND EXPLOSION HAZARD DATA

=====

Flash Point(Method Used): <50 F TCC Flammable Limits: LEL:N/A UEL: N/A

Extinguishing Media: CO2, FOAM, WATER, DRY CHEMICAL

Special Fire Fighting Procedures: SELF CONTAINED BREATHING APPARATUS.

Unusual Fire and Explosion Hazards: FLAMMABLE. CONTENTS UNDER PRESSURE. EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING. IGNITION MAY CAUSE RELEASE OF CARBON MONOXIDE AND CARBON DIOXIDE

Stability: Unstable: Conditions to avoid:
Stable: X TEMPERATURES ABOVE 120 F
Incompatibility (Materials to Avoid): STRONG OXIDIZING AGENTS

Hazardous Decomposition or Byproducts: NONE

Hazardous Polymerization: May Occur: Will Not Occur: X
Conditions to Avoid: NONE

Section VI: HEALTH HAZARD DATA

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES
Health Hazards (Acute and Chronic):
INHALATION: DIZZINESS AND NAUSEA. EXCESSIVE EXPOSURE MAY LEAD TO
UNCONSCIOUSNESS. SKIN: MAY CAUSE IRRITATION, DRYNESS. EYES: MAY CAUSE SOME
IRRITATION. INGESTION: NAUSEA. ASPIRATION MAY LEAD TO PULMONARY INJURY
Carcinogenicity: NTP:NO IARC Monographs:NO OSHA Reg:NO
Signs and Symptoms of Exposure: SEE HEALTH HAZARDS ABOVE

Medical Conditions Generally Aggravated by Exposure: MAY AGGRAVATE
DERMATITIS

Emergency and First Aid Procedures: INHALATION: REMOVE TO FRESH AIR AND SEE
PHYSICIAN. EYES: FLUSH WITH WATER IMMEDIATELY FOR 15 MINUTES. SEE
PHYSICIAN. SKIN: WASH THOROUGHLY WITH SOAP AND WATER. IF IRRITATION
PERSISTS, CONTACT PHYSICIAN. INGESTION: CONSULT PHYSICIAN IMMEDIATELY.

Section VII: PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled: WIPE UP WITH
RAG OR USE SOME ABSORBENT CLAY MATERIAL.

Waste Disposal Method: DISPOSE OF RESIDUE IN ACCORDANCE WITH FEDERAL,
STATE AND LOCAL GUIDELINES. DO NOT PUNCTURE OR INCINERATE CONTAINER. DO NOT
REUSE CONTAINER. WRAP AND PLACE IN TRASH COLLECTION.

Precautions to be Taken in Handling and Storing: DO NOT STORE NEAR HEAT OR
OPEN FLAMES. EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING.

Other Precautions: NONE

Section VIII: CONTROL MEASURES

Respiratory Protection: USE ONLY IN WELL VENTILATED AREA.
Ventilation: Local Exhaust: ADEQUATE
Mechanical: MAY BE NEEDED IN CONFINED S Special: N/A
Other: N/A
Protective Gloves: RECOMMENDED
Eye Protection: SAFETY GOGGLES ARE RECOMMENDED WHENEVER CHEMICALS ARE USED.
Other Protective Clothing or Equipment:
N/A
Work/Hygienic Practices:
WASH HANDS AFTER USE.