



# RPT-260 Wi-Fi Thermal Printer

## Feature

- Wireless port available
- Wall mount capable
- 200 mm/sec ultra-high speed printing
- support 80mm large diameter roll
- Support QR code printing
- Compatible with ESC/POS print instruction mode
- Support 256K NV logo download and print
- Easy paper jam clearance
- ESC/POS compatible
- Low-noise thermal printing
- Built-in interface provides control capability for Cash Drawer



## Applications

-  SUPERMARKET
-  MEDICAL CARE
-  STORAGE
-  POST
-  CATERING
-  STORE
-  TAX

## Technical Specification

MODEL	RPT-260Wi-Fi
Printing method	Direct thermal
Printing speed	200mm/s (RPT-260Wi-Fi)
Paper width	79.5±0.5mm
Printable area	72 mm (adjustable by commands)
Maximum Paper diameter	80 mm
Paper thickness	0.06-0.08mm
Column capacity	576 dots/line(adjustable by commands)
Line space	3.75mm (Adjustable by commands)
Commands	Compatible with ESC/ POS
Interface type	USB+Wi-Fi
Character size	ANK, Font A : 1.5×3.0mm (12×24 dots)
	Font B : 1.1×2.1mm (9×17 dots)
	Chinese,traditional Chinese:3.0×3.0mm (24×24 dots)
Dimension	184 ×140×142 mm (D×W×H)
Gross weight	1.0 kg
Bar code	UPC-A/UPC-E/JAN13, EAN13 / JAN8, EAN8 / CODE39/ITF/CODABAR/CODE93/CODE128
2-Dimension code	QR CODE / PDF417
Code page	sheet PC347 (Standard Europe), Katakana, PC850, (Multilingual), PC860, (Portuguese), PC863 (Canadian-French), PC865, Nordic), West Europe
	Greek, Hebrew, East Europe, Iran, WPC1252, PC866, (Cyrillic#2), PC852, (Latin2), PC858, IranII, Latvian, Arabic, PT151 (1251)
Cutter	Partial Cut
Cutter life	1.5 Million Cuts
Print head life	100 km
Input buffer	128 Kbytes
NV flash	256k bytes
Input voltage	DC 24V/2.5A
Cash drawer output	DC 24V/1A
Work environment	Temperature (0~45°C) humidity(10~80%)
Storage environment	Temperature(-10~60°C) humidity(10~80%)
Operating system	Windows/JPOS/Linux/Android/Mac
SDK	iOS, Android, Windows



**Phone: 9004566257 / 7738647344**

**Email: sales@realpostechonology.in**