



# HEAVY DUTY

## ROUND BALE TRANSPORTS

Just like everything manufactured at Central Welding Company, these bale transports are built to be tough. Unlike similar styled transports, our bale cradles are made from a continuous piece of 1/4 inch thick, 3 inch square tubing that is inserted through the 8X4X1/4 inch back bone. Once the cradles are welded in place, then a three foot long gusset made from 1/4 inch plate is added underneath each tube. By intersecting the main back bone with the cradles, an immense amount of strength is added to the frame. We also add bale stops between cradles to take the guess work out of when to stop when loading bales. We only use heavy duty 7500 pound rated, eight bolt agricultural hubs and spindles. We also add a rear mounted 2 inch hitch receiver tube on all models. We have models available in bumper pull, gooseneck, and tricycle style hitch.



## SERIOUS HAY HAULERS

AVAILABLE IN SIX,  
EIGHT, AND TEN BALE  
CAPACITIES

HEAVY DUTY 8 BOLT  
7500# HUBS AND  
TWELVE PLY TIRES

REAR HITCH  
RECEIVERS STANDARD  
ON ALL MODELS

### Central Welding Company

109 W Main St  
Concord, Illinois 62631  
(217) 457-2354

Visit us online at:  
[centralweldingco.com](http://centralweldingco.com)

Email:  
[central.welding.co@gmail.com](mailto:central.welding.co@gmail.com)



• **MODEL MBH1306 (6 BALE, BUMPER PULL)**

Rated at 10,500 lbs  
 Single axle  
 Comes with jack stands for field loading  
 Pin hitch  
 Heavy Duty 8 bolt Ag hubs and spindles rated at 7,500 lbs  
 12 ply 12.5I-15sl Implement tires  
 Standard implement red paint.

• **MODEL MBH1306G (6 BALE, GOOSENECK)**

Rated at 10,500 lbs  
 Single axle  
 Comes with jack stands for field loading  
 Gooseneck hitch, 2-5/16" ball coupler  
 Heavy Duty 8 bolt Ag hubs and spindles rated at 7,500 lbs  
 12 ply 12.5I-15sl Implement tires.  
 Standard implement red paint.

• **MODEL MBH1408G (8 BALE, GOOSENECK)**

Rated at 16,000 lbs  
 Single axle  
 Comes with jack stands for field loading.  
 Gooseneck hitch, 2-5/16" ball coupler  
 Heavy Duty 8 bolt Ag hubs and spindles rated at 7,500 lbs  
 12 ply 12.5I-15sl Implement tires.  
 Standard implement red paint.

• **MODEL MBH1408 (8 BALE, TRICYCLE FRONT WHEEL)**

Rated at 18,000 lbs  
 Single axle  
 Pin hitch, telescoping tongue  
 Heavy Duty 8 bolt Ag hubs and spindles rated at 7,500 lbs  
 12 ply 12.5I-15sl Implement tires.  
 Standard implement red paint.

**Available options include but, not limited to:**

- Tail Lights
- Custom Paint
- Plate Fenders
- Bale carriage over rear axles
- Walking beam rear axle
- Arched tongue (for bumper pull models)



Arched tongue option, designed to work in tandem with C2200 Bale Spear/Trailer Mover. Arched tongue allows spears to clear when turning.



Walking beam rear axle option with bale cradle over axles.



Research and Development



Rear View



Rear Hitch Receiver



Our Products Our Proudly Made In The U.S.A.