

Commercial Supplement

Customer Informati	ion:			Agent Information	ı <u>:</u>	
Entity Name:				Agent Name:		
Contact Name:				Agent Phone:		
				Agent Email:		
General Information	<u>n:</u>					
Effective Dates:				Competing Carrier:		
New Business or Renev	val:			Target (Including Fo	ees & Taxes): \$_	
Quote Type:						
Property Information	on:					
	Locati	on/Building 1	Location/	Building 2	Location/Bu	ilding 3
Address						
City/State/Zip						
Distance to Gulf						
Year Built						
Roof Updates						
Wiring Updates						
Plumbing Updates						
HVAC Updates	:					
Occupancy						
Construction						
Protection Class						
Roof Type						
Roof Shape						
Stories						
Fortified						
Alarm						
Opening Protection						
Percent Occupied						
Structure Type						
Exterior Finish						
Square Footage						
Tenant Type/Mix						
Coverage Information	Location #:	!	Building#:			
Subject of	Amount	Coinsurance	Valuation	Causes of Loss	AOP	Wind/Hail
Insurance	7 Imount	Comsurance	v uruution	Cuuses of Loss	Deductible	Deductible
				1		



Coverage Information: Location #: _____ Building#: ____

Subject of Insurance	Amount	Coinsurance	Valuation	Causes of Loss	AOP Deductible	Wind/Hail Deductible

Coverage Information: Location #: _____ Building#: ____

Subject of Insurance	Amount	Coinsurance	Valuation	Causes of Loss	AOP Deductible	Wind/Hail Deductible

Notes:

Frame Exterior walls are wood or other combustible material including brick veneer,

stone-veneer, wood iron clad, or stucco on wood.

Joisted Masonry (JM) Exterior walls are masonry, such as brick, concrete, gypsum block,

hollow concrete block, stone, tile, where roof and floors are combustible

Non-Combustible (NC) Exterior walls, floors, and roof are metal, gypsum, or other non combustible material

Masonry Non-Combustible

(MNC)

Exterior walls are same as (JM), but the floors and roof are metal, or other

non-combustible material

Modified Fire Resistive

(MFR)

Exterior walls, floors, and roof are masonry of fire resistive having a fire

resistive rating of less than 2 hours

Fire Resistive (FR) Exterior walls, floors and roof are masonry of fire resistive having a fire

resistive rating of more than 2 hours