

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

MINERAL STONE

TECHNICAL CHARACTERISTICS

Available Formats:	24x24		
Style Description:	Rustic Stone	Glaze Application Method:	H.D.I.T. Inkjet
Visual Characteristics:	Stone	Number of Faces/Screens:	4
Thickness in mm:	9.5	Number of Punches/Molds:	1
Modular Suitability:	No	Body Type:	Porcelain
Application:	Residential & Commercial	Color Body Unglazed:	White Body
Recycled Content: Post or Pre Customer	2%	Surface Type:	Matte
Rectified:	No	Recommended Grout Joint:	3/16 inches

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V4	Dynamic COF:	0.76
Scratch Hardness (MOHS)	6.5	Breaking Strength:	480 lbf
Frost Resistant:	No	Thermal Shock Resistance:	Do not present
PEI/Abrasion Resistance:	III	Deep Abrasion Test <175mm ² :	No
Chemical Resistance:	A		

PACKING INFORMATION - *Please inquire with Customer Service for additional sizes- 12x24*

SqFt per Carton:	15.18	Pieces per Carton:	4
SqFt per Pallet:	455.40	Pounds per Carton:	
Boxes per Pallet:	30	SqFt per Container:	
Pallets per Container:	27.00		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".