

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME

Borgia

## TECHNICAL CHARACTERISTICS

Available Formats:	30x30	Glaze Application Method:	H.D.I.T. Inkjet
Style Description:		Number of Faces/Screens:	8
Visual Characteristics:	Marble	Number of Punches/Molds:	
Thickness in mm:	10mm	Body Type:	Porcelain
Modular Suitability:		Color Body Unglazed:	No
Application:	Residential/Commercial	Surface Type:	Satin, Flat
Recycled Content: Post or Pre Customer		Recommended Grout Joint:	2mm
Rectified:	Yes		

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	<0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	<0.4
Scratch Hardness (MOHS)	5	Breaking Strength:	>35,0MPa
Frost Resistant:	No	Thermal Shock Resistance:	
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm <sup>2</sup> :	
Chemical Resistance:	>GLB		

## PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	18.62	Pieces per Carton:	3
SqFt per Pallet:	651.70	Pounds per Carton:	
Boxes per Pallet:	35	SqFt per Container:	
Pallets per Container:	20		

### Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".