

Profiles

Use: Roof/Wall/Liner
Slope: 3/12 and greater
Coverage: 36" width
Lengths: 3' to 45'


9-36



Recommended Substrate: Solid or Open Frame
Gauge: 29 ga, 26 ga, 24 ga **Exposed Fastener**

Use: Roof/Wall/Liner
Slope: 1/12 and greater
Coverage: 35" (26 ga), 36" (24ga)
Lengths: 3' to 45'


7/8" Corrugated



Recommended Substrate: Solid or Open Frame
Gauge: 26 ga, 24 ga, 22 ga **Exposed Fastener**

Use: Roof/Wall
Slope: 1/12 and greater
Coverage: 36" width
Lengths: 3' to 45'


12-36



Recommended Substrate: Solid or Open Frame
Gauge: 26 ga, 24 ga, 22 ga **Exposed Fastener**

Use: Roof/Wall
Slope: 3/12 and greater
Coverage: 36" width
Lengths: 3' to 45'


Diamond Rib



Recommended Substrate: Solid or Open Frame
Gauge: 26 ga, 24 ga **Exposed Fastener**

Use: Wall/Liner
Coverage: 36" width
Lengths: 3' to 45'


12-36 Reverse



Recommended Substrate: Solid or Open Frame
Gauge: 26 ga, 24 ga, 22 ga **Exposed Fastener**

Use: Wall/Liner
Coverage: 36" width
Lengths: 3' to 45'


Diamond Rib Reverse



Recommended Substrate: Solid or Open Frame
Gauge: 26 ga, 24 ga **Exposed Fastener**

Use: Curved Roof/Wall/Liner
Coverage: 36" width
Lengths: 3' to 45'


Low Rib



Recommended Substrate: Solid
Gauge: 29 ga, 26 ga **Exposed Fastener**

Use: Wall/Liner
Coverage: 37.25" (29 ga)
 41.25" (26 ga)
Lengths: 3' to 12'


Mesa



Recommended Substrate: Solid
Gauge: 29 ga, 26 ga **Exposed Fastener**

Use: Roof
Slope: 1/12 and greater
Coverage: 12" to 24" width
Lengths: 3' to 45'


Standing Seam



Recommended Substrate: Solid
Gauge: 26 ga, 24 ga, 22 ga **Hidden Fastener**

Use: Roof
Slope: 3/12 and greater
Coverage: 12" to 20" width
Lengths: 3' to 45'

Snaplock



Recommended Substrate: Solid
Gauge: 26 ga, 24 ga, 22 ga **Hidden Fastener**

*Available to Curve 1 1/2" height 24-22 ga only

