

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

Supreme

TECHNICAL CHARACTERISTICS

Available Formats:	24x48, 16x32, 12x24, 3x24 Bullnose, Rhomboid 9x10 Polished Mosaic Sheet		
Style Description:	Marble	Glaze Application Method:	H.D.I.T. Inkjet
Visual Characteristics:		Number of Faces/Screens:	20
Thickness in mm:	10mm	Number of Punches/Molds:	
Modular Suitability:	No	Body Type:	Porcelain
Application:	Residential	Color Body Unglazed:	
Recycled Content: Post or Pre Customer		Surface Type:	Polished
Rectified:	Rectified	Recommended Grout Joint:	

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	
Scratch Hardness (MOHS)	6	Breaking Strength:	
Frost Resistant:	Yes	Thermal Shock Resistance:	Resist
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm ² :	
Chemical Resistance:	Resist		

PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	13.11	Pieces per Carton:	7.00
SqFt per Pallet:	524.40	Pounds per Carton:	52.571
Boxes per Pallet:	40.00	SqFt per Container:	14683.20
Pallets per Container:	28.00		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".