

NEW PRODUCT SERIES

Technical Information Spec-sheet



**International
Wholesale
Tile, LLC**

NAME	SERIES	DECK
------	--------	------

TECHNICAL CHARACTERISTICS			
Available Formats:	12X48, 8X48		
Style Description:	Contemporary Wood Plank	Glaze Application Method:	HDIT Inkjet
Visual Characteristics:	Hand-Scraped	Number of Faces/Screens:	12 faces
Thickness in mm:	10mm	Number of Punches/Molds:	3
Modular Suitability:	Yes	Body Type:	Porcelain
Application:	Residential	Color Body Unglazed:	No
Recycled Content: Post or Pre Customer	NA	Surface Type:	Matte
Rectified:	Yes	Recommended Grout Joint:	1/16" to 3/16"

PRODUCT TESTING INFORMATION			
<i>Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)</i>			
Water Absorption:	<0.5%	Static COF:	Wet: Dry:
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	0.49
Scratch Hardness (MOHS)		Breaking Strength:	
Frost Resistant:	Yes	Thermal Shock Resistance:	NA
PEI/Abrasion Resistance:	4	Deep Abrasion Test <175mm ² :	No
Chemical Resistance:	Yes		

PACKING INFORMATION - 12x48 <i>Please inquire with Customer Service for additional sizes</i>			
SqFt per Carton:	11.63 sq ft	Pieces per Carton:	3
SqFt per Pallet:	302.38 sq ft	Pounds per Carton:	57.10 lbs
Boxes per Pallet:	26	SqFt per Container:	
Pallets per Container:			

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".