



Manufacturing Equipment for Abatement  
and Restoration Industry Since 1988

# MiniForce II

## HEPA Air Filtration Machine

**MiniForce II is a compact, portable HEPA air scrubber for small projects and restricted spaces. The MiniForce II is used as negative air machine for removal of toxic mold, asbestos and lead dust during renovation and abatement projects. For removal of chemical fumes, VOCs and biological contaminants, activated carbon filters can be installed.**

**The MiniForce II provides cleaner and healthier environment at construction/renovation projects and industrial facilities.**

### MiniForce II Specifications

<b>Airflow Ratings (cfm)*</b> .....	350 & 425
<b>Operating Speeds</b> .....	2 speeds
<b>Filtration Stages</b> .....	HEPA Filter 99.97%, 0.3µm
	.....MERV8 primary/secondary filter
<b>Optional</b> .....	OdorGuard 600 activated carbon filter
<b>Motor</b> .....	1/5 hp with Thermal Overload
<b>Circuit Requirements</b> .....	115V 60Hz 3.2 amps
<b>Pressure Gauge</b> .....	.0-3" W.C.
<b>Cabinetry</b> .....	Aluminum, silicone sealed before riveting
<b>Exhaust Collar</b> .....	8"
<b>Carrying Handles w/Rubber Grips</b> .....	1
<b>3" Hospital Grade Casters</b> .....	4 Swivel with Brakes
<b>Weight With Filters</b> .....	43 lbs.
<b>Dimensions</b> .....	26.5"L x 14"W x 16"H

\*Airflows based on blower manufacturer curves.

Different HEPA filters may cause the flow to vary.



CONFORMS TO UL STD 507  
CERTIFIED TO CAN/CSA STD  
C22.2 NO. 113-M1984

### ORDERING INFO ..... PART #

OmniAire MiniForce II .....	MF100C
HEPA Filter 99.97%, 0.3µm .....	MFH12
Primary/Secondary Filter (qty 20) ...	MFP1313
Intake Manifold, 8" .....	MFIM8
Quick Clamp, 8 to 10" .....	QCW12
Flexible Duct, 8" x 25' .....	MD8
OdorGuard 600 Carbon Filter .....	OG1212

## Omnitec Design, Inc.

4640 Campus Place, Suite 110 Mukilteo, WA 98275

Visit us @ [www.omnitecdesign.com](http://www.omnitecdesign.com)

Office: 425-290-3922