

4.000" OD, HWDP, INTEGRAL, STANDARD, 4.750" OD x 2.563" ID, VX39

## HEAVY WEIGHT DRILL PIPE BODY

Nominal OD (in)	4.000
Nominal ID (in)	2.563
Pipe Grade	ERS425
Heavy Weight Type	STANDARD
HWConstruction	INTEGRAL
Pipe Wall Thickness (in)	0.719
Cross Sectional Area of Pipe Body (in <sup>2</sup> )	7.407
Cross Sectional Area OD (in <sup>2</sup> )	12.566
Cross Sectional Area ID (in <sup>2</sup> )	5.159
Section Modulus (in <sup>3</sup> )	5.224
Polar Section Modulus (in <sup>3</sup> )	10.448
Torsional Strength (lbs/ft)	55,300
Tensile Strength (lbs)	815,000
Burst Pressure (psi)	39,500
Collapse Pressure (psi)	32,400

## HEAVY WEIGHT DRILL PIPE CONNECTION

OD (in)	4.750
ID (in)	2.563
Pin Tong Length (in)	27.00
Box Tong Length (in)	21.00
Connection	VX39
Torsional Strength (lbs/ft)	27,900
Tensile Yield Strength (lbs)	719,000
Minimum Make-up Torque (lbs/ft)	15,100
Recommended Make-up Torque (lbs/ft)	16,700
Maximum Make-up Torque (lbs/ft)	17,600
Tool Joint/Drill Pipe Torsional Ratio (New)	0.50
Balanced OD	5.070

## HEAVY WEIGHT DRILL PIPE ASSEMBLY

Approx Average Length (ft)	31.50
Open End Displacement (gal/ft)	0.43
Closed End Displacement (gal/ft)	0.70
Fluid Capacity (gal/ft)	0.27
Drift Size (in)	2.438
Adjusted Weight (lbs/ft)	28.21
Hardbanding	DURABAND NC

All information contained herein is provided for reference/illustration purpose only. Data compiled are using information available from respective Manufacturer and/or other public sources. Even though due care has been exercised while compiling the data. PETRO PIPE accept no responsibility or liability for its accuracy, errors, omissions or misinterpretation. User is advised to examine the suitability and accuracy by their own resources.