NEW PRODUCT SERIES

Technical Information Spec-sheet



SERIES NAME	VERONA
-	

TECHNICAL CHARACTERISTICS					
Available Formats:	24x24, 12x24, 2x2 Mosaic 12x12 Sheet, 3x24 Bullnose				
Style Description:	Marble	Glaze Application Method:	HDIT Inkjet		
Visual Characteristics:	Polished Marble	Number of Faces/Screens:	N/A		
Thickness in mm:	10.2mm-10.3mm	Number of Punches/Molds:	1		
Modular Suitability:	No	Body Type:	Porcelain (< .5%)		
Application:	Residential/Commercial	Color Body Unglazed:	No		
Recycled Content:	N/A	Surface Type:	Polished with Nano		
Post or Pre Customer			Finish/Confirmed Sealed		
Rectified:	Yes	Recommended Grout Joint:	No less than 1/8"		

PRODUCT TESTING INFORMATION					
Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)					
Water Absorption:	< .5%	Static COF:	N/A		
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	N/A		
Scratch Hardness (MOHS)	5	Breaking Strength:	1483~1577N		
Frost Resistant:	Yes	Thermal Shock Resistance:	Yes		
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm ² :	Yes		
Chemical Resistance:	Grade GA				

PACKING INFORMATION - 24x24 Please inquire with Customer Service for additional sizes			
SqFt per Carton:	15.5	Pieces per Carton:	4
SqFt per Pallet:	620.00	Pounds per SqFt:	4.7 lbs
Boxes per Pallet:	40	SqFt per Container:	13,020
Pallets per Container:	21		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".