

NEW PRODUCT SERIES

Technical Information Spec-sheet



**International
Wholesale
Tile, LLC**

SERIES NAME

Epoque

TECHNICAL CHARACTERISTICS

Available Formats:	10x60, 30x30		
Style Description:	Wood Plank w Cement Blend Inlay	Glaze Application Method:	H.D.I.T. Inkjet
Visual Characteristics:		Number of Faces/Screens:	15
Thickness in mm:	9mm	Number of Punches/Molds:	8
Modular Suitability:	No	Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	UGL
Recycled Content: Post or Pre Customer		Surface Type:	Matte/Textured
Rectified:		Recommended Grout Joint:	

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	0.20%	Static COF:	
Shade Variation (1, 2, 3, 4)	3	Dynamic COF:	>0.42
Scratch Hardness (MOHS)		Breaking Strength:	>35 n/MMQ
Frost Resistant:	Yes	Thermal Shock Resistance:	Resists
PEI/Abrasion Resistance:	5	Deep Abrasion Test <175mm ² :	
Chemical Resistance:			

PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	12.16	Pieces per Carton:	2
SqFt per Pallet:	510.72	Pounds per Carton:	53.7472
Boxes per Pallet:	42	SqFt per Container:	
Pallets per Container:			

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".