



# PowerSafe® DU

Telecommunications

NEBS™ Certified

## Battery Range Summary



The PowerSafe® DU battery series has been designed to handle the demanding float and deep discharges typical for telecommunication applications. The DU battery series features proven flat plate lead-calcium grid alloy and is the largest amp hour capacity four cell battery in the industry ranging from 310 to 780Ah. The DU series multi-cell construction shortens installation time and reduces the battery string footprint.

The DU battery series has been designed with the edge of the plates oriented perpendicular to the rack rails for full plate edge visibility. The dual hole (top/bottom) terminal design allows for easy maintenance.

The DU battery series employs the EnerSys® proven Slide-Lock™ post seal that allows for natural plate growth over time without degrading the seal. The innovative tongue-and-groove jar-to-cover seal provides reliability with a robust airtight seal.

### Features and Benefits

- Capacity Range: 310 – 780Ah
- Flat plate, lead-calcium grid alloy, well suited for long duration float applications
- Proven Slide-Lock™ post seal design
- Positive and negative posts on each cell allow for monitoring of individual cells
- Standard UL94 V-0 flame retardant cover and container
- NEBS™ level 3 certified for systems with a nominal voltage under 80V
- Application: suitable for installation in network telecommunication facilities
- 20 year life expectancy in float service at 77°F (25°C) ambient temperature

Visit us at [www.enersys.com](http://www.enersys.com)

**EnerSys**  
Power/Full Solutions

RESERVE  
POWER

Publication No: US-DU-RS-001 - October 2013

## Construction

- 0.25" thick positive plates provide long discharge rates and long life
- Lead plated copper posts - one positive and one negative post per cell
- Cover - standard PVC UL94 V-0 LOI>28%  
Container - standard PC UL94 V-0 LOI>28%
- Separator - microporous phenolic with "Vitrex" glass fiber retainers
- 1.215 specific gravity nominal at 77°F (25°C)
- Intercell connectors - lead-plated copper, optional tin-plated copper
- Proven Slide-Lock™ post seal design

## Installation and Operation

- Maintenance connectors available
- Flat plate, lead-calcium grid alloy, well suited for long duration float applications
- 20 year life expectancy in float service at 77°F (25°C) ambient temperature
- Operating temperature: 32°F (0°C) to 104°F (40°C)  
Recommended temperature: 68°F (20°C) to 86°F (30°C)

## Standards

- The management systems governing the manufacture of this product are ISO 9001:2008 and ISO 14001:2004 certified

## General Specifications

Cell Type*	Nominal Ah Capacity <sup>1</sup>	Nominal Dimensions								Weight - Volumes					
		Length**		Width		Height		Height***		Unpacked		Electrolyte only 1.215 S.G.			
		in	mm	in	mm	in	mm	in	mm	lbs	kg	lbs	kg	gal	liters
4DU-05	310	9.5	241	16.0	406	22.7	576	26.9	683	267	121	64	29	6.3	24
4DU-07	395	9.5	241	16.0	406	22.7	576	26.9	683	328	149	59	27	5.8	22
4DU-09	625	16.7	424	16.0	406	22.7	576	28.8	732	494	224	134	61	13.2	50
4DU-11	715	16.7	424	16.0	406	22.7	576	28.8	732	555	252	123	56	12.2	46
4DU-13	780	16.7	424	16.0	406	22.7	576	28.8	732	617	280	113	51	11.1	42

\* Prefix number indicates cells per unit. Suffix number indicates total plates per cell.

\*\* 0.25" must be added between units for spacing purposes when calculating total battery length.

\*\*\*Includes height to top of terminal plate.

<sup>1</sup> Nominal Ah capacity is based on an 8 hour rate to 1.75 volts per cell @ 77°F (25°C).

<sup>1</sup> Values listed represent 100% of the cell's capacity. Initial capacity shall be minimum of 90% of these values per IEEE 450.

