

RFID READER

Plastic IC/ ID Reader



ESS® 502-902 series

Plastic RFID Card Reader

- Wiegand Wg26 I/O, Wg34 (optional)
- EM 125KHz, Mifare, HID
- Reading Range: 5-10cm for EM, 5-8cm for Mifare, 5-6cm for HID
- Plastic, Black
- 110x50x18mm
- Weight: 220g

MODEL #	FREQUENCY, Hz
502-902E	EM ID 125KHz
502-902H	HID 125KHz
502-902M	Mifare IC 13.56MHz

Plastic RF Card Reader



- IC/ ID card
- Output:Wg26, Wg34 (optional)
- Static electricity: ≤30mA
- 110x86x18mm

MODEL #	Hz
502-903E	ID 125KHz
502-903M	IC 13.56MHz

Plastic RF Card Reader



- IC/ ID card
- Output:Wg26, Wg34 (optional)
- 100x46x20mm

MODEL #	Hz
501-R19E	ID 125KHz
501-R19M	IC 13.56MHz

Plastic RF Card Reader



- IC/ ID card
- Output:Wg26, Wg34(optional)
- 80x80x20mm

MODEL #	Hz
501-R20E	ID 125KHz
501-R20M	IC 13.56MHz

Plastic RF Card Reader



- IC/ ID card
- Output:Wg26, Wg34 (optional)
- 100x46x18mm

MODEL #	Hz
501-R85E	ID 125KHz
501-R85M	IC 13.56MHz

Plastic RF Card Reader



- IC/ ID card
- Output:Wg26, Wg34 (optional)
- 86x86x18mm

MODEL #	Hz
501-R86E	ID 125KHz
501-R86M	IC 13.56MHz

Plastic RF Card Reader



- IC/ ID card
- Output:Wg26
- 82x42x15mm

MODEL #	Hz
502-991E	ID 125KHz
502-991M	IC 13.56MHz