

## Standard Enclosure Terminals, 380...480 Volt Units

380...480 Volt		Frame Size	Maximum Wire Size Capacities of Power Terminals				
HP	Identification		Circuit Breaker	Disconnect Switch	Motor Terminal Block	Ground Lugs	
1/1.5	ACH550-BxR-03A3-4	R1	#8 40 in-lbs	#8 7 in-lbs	#6 15 in-lbs	#4 35 in-lbs	
2	ACH550-BxR-04A1-4	R1					
3	ACH550-BxR-06A9-4	R1					
5	ACH550-BxR-08A8-4	R1					
7.5	ACH550-BxR-012A-4	R1					
10	ACH550-BxR-015A-4	R2					
15	ACH550-BxR-023A-4	R2					
20	ACH550-BxR-031A-4	R3	#1 50 in-lbs	#4 18 in-lbs	#2 50 in-lbs	#2 50 in-lbs	
25	ACH550-BxR-038A-4	R3					
30	ACH550-BxR-045A-4	R3					
40	ACH550-BxR-059A-4	R4					
50	ACH550-BxR-072A-4	R4					
60	ACH550-BxR-078A-4	R4					
75	ACH550-BxR-097A-4	R4	350 MCM 274 in-lbs	#1/0 70 in-lbs	#1 53 in-lbs	3 x #3/0 250 in-lbs	
100	ACH550-BxR-125A-4	R5		300 MCM 275 in-lbs	250 MCM 300 in-lbs		400 MCM 375 in-lbs
125	ACH550-BxR-157A-4	R6					
150	ACH550-BxR-180A-4	R6					
200	ACH550-BxR-246A-4	R6	2 x 250 MCM 274 in-lbs	2 x 250 MCM 274 in-lbs	2 x 500 MCM 375 in-lbs	5 Bus bar holes (13/32" bolts)	
250	ACH550-BxR-316A-4	R8	2 x 500 MCM 274 in-lbs	2 x 500 MCM 275 in-lbs	2 x 600 MCM 500 in-lbs		
300	ACH550-BxR-368A-4	R8					
350	ACH550-BxR-414A-4	R8					
400	ACH550-BxR-486A-4	R8					