

MODEL HR 9 ROTAVATOR®

Tillage Widths of 50" & 60"... for Tractors from 25 H.P. to 45 H.P.

The Model HR 9 ROTAVATOR is a truly versatile tiller designed for small farms; fruit, vegetable and other specialized crops; plus nursery and landscaping operations. It prepares perfect seedbeds, incorporates crop residues or chemicals and provides effective weed control. Since this hardworking ROTAVATOR does the job of a plow, disc and harrow in a single pass, it reduces compaction in addition to improving soil structure and controlling erosion. Efficient and dependable, the HR 9 ROTAVATOR helps conserve your soil while saving on tillage costs.



MODEL HR 9 ROTAVATOR

A MID-SIZED ROTAVATOR WITH A BIG ENGINEERING TRADITION

Over 50 years of engineering excellence have made Howard the world leader in rotary tillage equipment. The Model HR 9 ROTAVATOR is heir to this long tradition. Like its cousins in the extensive Howard line, it offers features and durability you would expect only in a much larger tiller.



HANDLES TOUGH PRIMARY TILLAGE JOBS

A heavy-duty rotor and rugged Howard blades make the Model HR 9 an efficient performer even in compacted soils.

In the fall, a single pass produces a coarse tilth to hold winter moisture and promote soil "mellowing." Crop residues can be chopped and mixed in at the same time to control erosion and improve soil structure.

SAVES ON SECONDARY SEEDBED TILLAGE

In the spring, the HR 9 easily prepares a perfect seedbed in fewer passes than conventional tillage tools. The rotating blades create an even mixture of humus-producing materials while keeping the rich topsoil where it's needed most—on top!


This humus-producing blend promotes faster spring warm-up and better moisture retention for earlier germination and a stronger, more uniform stand.

A TRUE MULTI-PURPOSE IMPLEMENT

In addition to crop residues, the HR 9 ROTAVATOR also incorporates fertilizers and herbicides at an adjustable and accurate tillage depth. Field tests show the resulting mix is far superior to that produced by other tillage equipment.

CENTER OR OFFSET MOUNTING

The versatile Model HR 9 can be mounted centrally or offset behind the tractor. This makes it the ideal implement for cultivating in busy nurseries, orchards, groves and berry farms—working closely around plants, shrubs and young trees without damage. Weed control was never easier! Inherent ROTAVATOR toughness also makes the HR 9 a natural choice for demanding landscaping operations.



MANY MODELS TO CHOOSE FROM

Howard manufactures a full line of ROTAVATORS for all crops and every tillage need. Choose models from 32 inches to 240 inches wide for 10 H.P. to 250 H.P. tractors. Contact your local Howard dealer or write direct for complete details.

SPECIFICATIONS

Tillage Widths: 50" & 60"

Power Range: For tractors from 25 to 45 H.P. with 540 rpm PTO.

Linkage: Category I, 3-point hitch.

Tillage Depth: Adjustable to 7" via twin skids.

Rotor Speed: 209 rpm.

Machine Weights: 50" - 565 lbs., 60" - 630 lbs.

DEALER



Howard Rotavator Company, Inc. A Member of the Howard Group 102 Howard Ave., P.O. Box 7, Muscoda, Wisconsin 53573 (608) 739-3106 Branch in Sacramento, California 95821 (916) 483-2777

HOWARD® PARAPLOW® ROTASPIKE® ROTAVATOR® SELECTATILTH® TURF-QUAKER®

are registered trademarks of HOWARD ROTAVATOR COMPANY.









