



## ZPMV2.E115009 Wiring, Printed - Component

For enhanced search functionality, please visit UL's [iQ™ Family of Databases](#).  
Click on a product designation for complete information.

[Page Bottom](#)

## Wiring, Printed - Component

[See General Information for Wiring, Printed - Component](#)

**CIRCUIT CONNECT INC**  
4 STATE ST  
NASHUA, NH 03063 USA

E115009

	Cond Width		Cond	SS/ DS/	Max Area	Solder Limits	Max Oper Temp	Max Flame Class	Meets UL796	C	
	Min	Edge									
Type	mm(in)	mm(in)	Thk mic(mil)	DSO	Diam mm(in)	C	sec	C	Class	DSR	I
<b>Mass-laminated printed wiring boards.</b>											
<b>8</b>	0.13 (0.005)	0.38 (0.015)	16.5 (0.65)	DS	76.2 (3.0)	260	10	105	VTM-1	-	-
<b>Multilayer printed wiring boards.</b>											
<b>10</b>	0.08 (0.003)	0.24 (0.009)	17 (0.67) Int:132	DS	76.2 (3.0)	257	3	130	V-0	All	3
<b>10D</b>	0.09 (0.004)	0.11 (0.004)	17 (0.67) Int:68	DS	76.2 (3.0)	260	10	130	V-0	All	-
<b>11</b>	0.08 (0.003)	0.24 (0.009)	17 (0.67) Int:132	DS	76.2 (3.0)	257	3	130	V-0	All	3
<b>12</b>	0.08 (0.003)	0.24 (0.009)	17 (0.67) Int:132	DS	76.2 (3.0)	257	3	130	V-0	All	3
<b>6</b>	0.13 (0.005)	0.38 (0.015)	17 (0.67) Int:68	DS	76.2 (3.0)	260	10	130	V-0	All	*
<b>CC-4A</b>	0.1 (0.004)	0.15 (0.006)	17 (0.67) Int:35	DS	90 (3.5)	288	10	130	V-0	All	*
<b>CC-6</b>	0.07 (0.003)	0.12 (0.005)	17 (0.67) Int:68	DS	76.2 (3.0)	260	10	130	V-0	All	*
<b>CC-6A</b>	0.31 (0.012)	0.47 (0.019)	103 (4.06) Int:103	DS	30 (1.2)	260	10	130	V-0	All	3
<b>CC-6C</b>	0.1 (0.004)	0.1 (0.004)	17 (0.67) Int:68	DS	50.8 (2.0)	260	5	120	V-0	All	-
<b>Single layer printed wiring boards.</b>											
<b>2, B</b>	0.25 (0.010)	0.76 (0.030)	17 (0.67)	DS	63.5 (2.5)	260	10	130	V-0	All	*
<b>4</b>	0.1 (0.004)	0.1 (0.004)	17 (0.67)	DS	304.8 (12.0)	260	10	130	V-0	All	*
<b>4D</b>	0.09 (0.004)	0.11 (0.004)	17 (0.67)	DS	76.2 (3.0)	260	10	130	V-0	All	-
<b>A</b>	0.25 (0.010)	0.76 (0.030)	17 (0.67)	DS	63.5 (2.5)	260	10	130	V-0	All	*
<b>CC-2</b>	0.07 (0.003)	0.13 (0.005)	17 (0.67)	DS	76.2 (3.0)	260	10	130	V-0	All	*
<b>CC-2A</b>	0.1 (0.004)	0.15 (0.006)	17 (0.67)	DS	90 (3.5)	288	10	130	V-0	All	*
<b>CC-3A</b>	0.31 (0.012)	0.47 (0.019)	103 (4.06)	DS	30 (1.2)	260	10	130	V-0	All	3
<b>CC-4C</b>	0.1 (0.004)	0.1 (0.004)	- Int:35	DS	25.4 (1.0)	260	5	120	V-0	All	-

\* - CTI PLC is marked on individual board.

