

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

Yosemite

TECHNICAL CHARACTERISTICS

Available Formats:	36x36, 24x24, 12x24, 3x24 Bullnose		
Style Description:		Glaze Application Method:	H.D.I.T. Inkjet
Visual Characteristics:	Limestone	Number of Faces/Screens:	36x36: 16, 24x24: 32, 12x24: 64
Thickness in mm:	11 (cm90x90) - 10mm (CM60x60- cm30x60)	Number of Punches/Molds:	1
Modular Suitability:	No	Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	Colored
Recycled Content: Post or Pre Customer	40%	Surface Type:	Matte, Flat
Rectified:	Yes	Recommended Grout Joint:	3/16"

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	≥0.42
Scratch Hardness (MOHS)	7.5	Breaking Strength:	
Frost Resistant:	Yes	Thermal Shock Resistance:	Yes
PEI/Abrasion Resistance:	V2	Deep Abrasion Test <175mm ² :	
Chemical Resistance:			

PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	17.44	Pieces per Carton:	2
SqFt per Pallet:	523.20	Pounds per Carton:	
Boxes per Pallet:		SqFt per Container:	
Pallets per Container:	17		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".