

# NEW PRODUCT SERIES

Technical Information Spec-sheet



**International  
Wholesale  
Tile, LLC**

SERIES NAME

**Pietra Tiburtina**

## TECHNICAL CHARACTERISTICS

Available Formats:	24x24, 12x24, 12x12, 3x12, Intreccia Mosaic 12x12 Sheet		
Style Description:		Glaze Application Method:	H.D.I.T Inkjet
Visual Characteristics:	Stone	Number of Faces/Screens:	24:18, 12x24:36
Thickness in mm:	10mm	Number of Punches/Molds:	3
Modular Suitability:	Yes	Body Type:	Porcelain
Application:	Residential / Commercial	Color Body Unglazed:	No
Recycled Content: Post or Pre Customer		Surface Type:	Matte
Rectified:	No	Recommended Grout Joint:	4mm

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	<0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	≥0.42
Scratch Hardness (MOHS)	6	Breaking Strength:	≥35 N/mm <sup>2</sup>
Frost Resistant:	Yes	Thermal Shock Resistance:	
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm <sup>2</sup> :	
Chemical Resistance:	Class GLA		

## PACKING INFORMATION - 24x24 *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	11.94	Pieces per Carton:	3
SqFt per Pallet:	382.08	Pounds per Carton:	52.66
Boxes per Pallet:	32	SqFt per Container:	12608.64
Pallets per Container:	33		

### Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".