

CONCRETECH

Acrylic Waterbase Sealer

PRODUCT DESCRIPTION

Acrylic Waterbase Sealer is a high performance 100% Acrylic finish coat. A 4-mil (wet) coat will provide transparent, high gloss, abrasion resistant finish with minimum surface preparation.

USES

Acrylic Waterbase Sealer is recommended for exterior and interior applications. It is specially used where humidity and rain are a main concern.

BENEFITS

- High Gloss
- Rapid Drying
- UV Resistant
- Abrasion Resistant
- Wet Adhesion
- Good Adhesion to Chalky Concrete
- Easy to Apply
- Excellent Efflorescence Resistance

PACKAGING

Acrylic Waterbase Sealer is available in 18.9L / 5 Gal. Plastic Containers

LIMITATIONS

Inspect all surfaces to ensure that they are sound, free of sealer, wax or oil. Surface preparation is the most important aspect in obtaining desirable results. Remove loose materials from the surface. Existing concrete surfaces should be scrubbed with a commercial degreaser (Concretech R/A Soap) using a red or black buffer pad on a commercial floor maintainer. Dispose the wash-offs in accordance with federal, state, and local regulations. Do not apply at temperatures below 10°C (50°F)

INSTALLATION INSTRUCTIONS

Surfaces should be clean, dry and sound. Remove surface laitance. Application can be done with spray, short knap roller, squeegee or brush. May be thinned up to 5% with water if required. Two thin coats are better than one thick coat. First coat should touch dry and

clear before applying second coat. The surface needs light sanding if recoated after 24 hours. Damp concrete floors will get wet faster and achieve better adhesion.

STORAGE AND HANDLING

Storage: Shelf life of one-year from date of manufacture in protected area at 5°C - 30°C (40-85°F). Store in a dry place.

Handling: Avoid prolonged or repeated skin contact. Wash hands thoroughly after handling and before eating or drinking. Keep away from children. See MSDS for additional information.

PROPERTIES

Analysis

Non Volatile (Wt)	30 %
Non Volatile (Vol)	27.3 %
Specific Gravity	1.037g/m ³
VOC, lbs/gal	0.21
VOC, g/l	25

Dry Time @ 25°C (77°F)

Tack Free	½ Hour
Thorough Dry	1 Hour
Hard Dry	24 Hours

Coverage is 400 SqFt. / 3.78 L. (1 Gal.)
2000 SqFt. / 18.9 L. (5 Gal.)

TECHNICAL SERVICES

Complete technical information is available from Concretech Inc. and its authorized applicators and distributors. In house laboratory testing is available for specialty applications. Technical services available in North America call toll free 1.888.503.6780

Concretech Inc's sole warranty is that our products have been manufactured to meet with our written specifications. The information herein is general information to assist our customers in determining whether our products are suitable for their applications. Our products are intended for sale to commercial and industrial customers. We require customers to inspect and test our products before use and to satisfy themselves as to contents, suitability and applications. Nothing herein shall constitute any other warranty, express or implied, including any warranty of merchantability or fitness for a particular purpose, nor is any protection from any law or patent inferred. All patent and trademark rights are reserved. The exclusive remedy for all proven claims is replacement of our materials and in no event shall we be liable for incidental or consequential damages.

CONCRETECH

104, 2567 192 Street
Surrey, BC V3S 3X1
www.concretechproducts.com

Toll Free: 1.888.503.6780
Fax: 1.604.357.1344
Tel. 1.604.210.1147