



V-Lux Technical Specifications

Description: Luxury Engineered Vinyl Plank, Floating Floor with Attached IXPE Pad

Warranty: Limited Lifetime Residential Wear Warranty
10 Year Limited Light Commercial Warranty

Installation: Unilin Click - Float, Glue Down

Construction: Stone Core Composite (70% Limestone with virgin PVC)
V-Lux – 12 mil wear layer with 1.0 mm IXPE Pad

Size/Packing: V-Lux – 12” x 24” x 5mm: 4.0 mm Core + 1.0 mm IXPE Pad
24.00 sf/box, 12 Pc. per/box, 54 boxes/pallet

Wear Finish: 2 layered Ceramic Bead, Aluminum Oxide Finish with Antimicrobial surface

TEST DATA

ASTM – E90-09 Airborne Sound Conduction:	STC 53 db
ASTM – E492-09 Impact Insulation Class:	IIC 54 db / ΔIIC 21
ANSI A137.1 Dynamic Coefficient of Friction Test:	0.52 DCOF
ASTM F-970-00 Static Load Limit:	1500 PSI (0.008 of an inch)
ASTM F 1515 Color Resistance to Light:	Meets <8.0 Δ E Requirement
ASTM F 1514 Color Resistance to Heat:	Meets <8.0 Δ E Requirement

See Website for additional testing.

