



- 1. SEE CROSS SECTION FOR METHOD OF ROOF VENTILATION
- 2. FOUNDATION ENCLOSURE (WHEN PROVIDED) MUST HAVE ONE SQUARE FOOT NET VENT AREA PER 1/150TH OF THE FLOOR AREA.
- 3. A 22"X36" MINIMUM CRAWL SPACE ACCESS AND A 6 MIL POLY GROUND COVER, SITE INSTALLED BY OTHERS AND SUBJECT TO LOCAL JURISDICTION.
- 4. STEPS, RAILS, & DECKS TO BE DESIGNED AND BUILT BY OTHERS ON SITE, IN ACCORDANCE WILL LOCAL CODES REQUIREMENTS AND INSPECTIONS.



Aug 02, 2017

FINER LINES DESIGN & CONSTRUCTION INC.

DATE:	7/24/2017	3RD PARTY INSPECTION AGENCY
CODES:	2014 FBC	NTA INC 305 NORTH OAKLAND AVE NAPPANEE, IN 48550 Contact: Dave Borts (574-773-27
LABELS:	FLORIDA	
SCALE:	NTS	

MODEL:
MFT2437-ME483-680-108

DRAWN BY:
Jerry Benton
DRAWING:

EXTERIOR ELEVATION

RIK MYERS PE, PLL 2805 28TH STREET