

VIDEO PROFESSIONAL WHEEL BALANCER FOR TIRE DEALERS



1946

ER73

PERFECT BALANCING IN JUST ONE SPIN

ER73TD WHEEL BALANCER

is made especially for busy tire shops and tire dealers. This new series has the latest technology in wheel balancing: "Spotter" laser that actually pinpoints the exact location for the placement of stick-on wheel weights.

CEMB[®]^USA

ER73TD spotte

1.0

ER73

Power requirements

Unbalance resolution Rim width setting range Rim diameter setting range Max. tire diameter Max. wheel weight Shaft diameter

Measuring cycle for 15 kg (33 lbs) wheel

Balancing speed

Machine weight

 STATIC UNBALANCE ALWAYS DISPLAYED ON SCREEN for full-time accuracy

CEMB[®] PATENT

- VDD Virtual Direct Drive Quick measurement system
- NEW AUTOMATIC ARM to measure automatically diameters up to 30"
- EMS RUNOUT SONAR (optional): Automatic and quick radial runout measurement with sonar during normal balancing cycle
- ELECTROMAGNETIC BRAKE holds the wheel in position
- Designed especially for tire dealers



STANDARD ACCESSORIES





OPTIONAL ACCESSORIES

RL CUP - 41FF79255 SR-USA STUD ADAPT. - 41FF56189 SRU345 STUD ADAPT. - 41FFA6478 2-PIECE TRUCK CONE KIT - 41FF86174 CERTIFICATE PRINTER - 860P63297 WBL81 WHEEL LIFT - 46FL85170-KIT

MANUAL LOCKING

For a complete list of accessories and more information visit our website www.cemb-usa.com

WIDTH SONAR 3D for automatic measurement of wheel width

Made in ITALY

 LED to light the work space inside the rim



SPOTTER LASER SYSTEM Fully automatic spot-on laser for best and quickest correction possible (no manual operations)

110 VAC	
100 rpm	
4.7 s	
< 0.01 oz (<1 g)	
1.5" - 20" (40 - 510 mm)	
10" - 30" (265 - 765 mm)	
42" (1,067 mm)	
165 lbs (75 Kg)	
40 mm	
390 lbs (177 Kg)	

CEMB® USA - BL Systems Inc. 2873 Ramsey Road, Gainesville GA 30501 - USA Phone +1 (678) 717-1050 - sales@cemb-usa.com www.cemb-usa.com

DISTRIBUTED BY

Because of continuing technological advancements, specifications, models and options are subject to change without notice