

NEW PRODUCT SERIES

Technical Information Spec-sheet



**International
Wholesale
Tile, LLC**

SERIES NAME

NATURALIA

TECHNICAL CHARACTERISTICS

Available Formats:	6x40	Glaze Application Method:	HDIT Inkjet
Style Description:	Waxed Wood	Number of Faces/Screens:	25
Visual Characteristics:	Wood	Number of Punches/Molds:	N/A
Thickness in mm:	10 mm	Body Type:	Porcelain (<.5%)
Modular Suitability:	No	Color Body Unglazed:	No
Application:	Residential/Commercial	Surface Type:	Matte
Recycled Content: Post or Pre Customer	40%	Recommended Grout Joint:	Minimum 3/16"
Rectified:	No		

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<.5%	Static COF:	Wet: 0.61 Dry: 0.74
Shade Variation (1, 2, 3, 4)	V4	Dynamic COF:	0.53
Scratch Hardness (MOHS)	7	Breaking Strength:	450
Frost Resistant:	Yes	Thermal Shock Resistance:	Yes
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm ² :	Yes
Chemical Resistance:	Yes		

PACKING INFORMATION

SqFt per Carton:	13.23	Pieces per Carton:	8
SqFt per Pallet:	555.66	Pounds per Carton:	59 Lbs
Boxes per Pallet:	42	SqFt per Container:	N/A
Pallets per Container:	N/A		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".