

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

REAL CHARM

TECHNICAL CHARACTERISTICS

Available Formats:	6x36, 3x24, 10x11 Hex		
Style Description:		Glaze Application Method:	H.D.I.T. Inkjet
Visual Characteristics:	Reclaimed Wood	Number of Faces/Screens:	6x36 (39), 3x24(40), 10x11 Hex (24)
Thickness in mm:	10 mm	Number of Punches/Molds:	
Modular Suitability:	No	Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	
Recycled Content: Post or Pre Customer	3	Surface Type:	Matte
Rectified:	Pressed	Recommended Grout Joint:	3mm

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	E<0,1 BLA- GL	Static COF:	
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	>0,42
Scratch Hardness (MOHS)	>6	Breaking Strength:	
Frost Resistant:	Yes	Thermal Shock Resistance:	resistent
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm ² :	No
Chemical Resistance:	Class A-LA-HA (No Hydrofluoric acid)		

PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	13.13	Pieces per Carton:	9
SqFt per Pallet:	630.24	Pounds per Carton:	
Boxes per Pallet:	48	SqFt per Container:	
Pallets per Container:	22		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".