

IES1450 SAFETY DATA SHEET.

Issuing date 08-Jun-2015

Revision Date 08-Jun-2015

Version 1.02

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING**Product identifier****Product name** 1450 BRAKE SILENCER**Recommended use of the chemical and restrictions on use****Product code** 1450**Product Type** Highly Flammable Liquid and Vapor
Synonyms None**Supplier's details****Recommended Use** Brake Silencer.
Uses advised against No information available**Manufacturer:**
International Epoxies & Sealers
P.O. Box 185
San Antonio, FL 33576**Emergency telephone number****Chemical Emergency Phone Number** INFOTRAC 1-352-323-3500 (International)
1-800-535-5053 (North America)
Emergency telephone INTERNATIONAL EPOXIES & SEALERS 1-800-451-7206

2. HAZARDS IDENTIFICATION

Classification


Serious eye damage/eye irritation	Category 2A
Specific target organ toxicity (single exposure)	Category 3
Flammable Liquids	Category 2

GHS Label elements, including precautionary statements

Emergency Overview

DANGER

Hazard Statements
 Causes serious eye irritation
 May cause drowsiness or dizziness
 Highly flammable liquid and vapor



Appearance opaque **Physical state** Liquid **Odor** Solvent

Precautionary Statements - Prevention

- Wash face, hands and any exposed skin thoroughly after handling
- Avoid breathing dust/fume/gas/mist/vapors/spray
- Wear protective gloves/eye protection/face protection.
- Use only outdoors or in a well-ventilated area
- Keep away from heat/sparks/open flames/hot surfaces. — No smoking
- Keep container tightly closed
- Ground/Bond container and receiving equipment
- Use explosion-proof electrical/ventilating/lighting /equipment.
- Use only non-sparking tools
- Take precautionary measures against static discharge

Precautionary Statements - Response

- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- If eye irritation persists: Get medical advice/attention
- IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
- IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- Call a POISON CENTER or doctor/physician if you feel unwell
- In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

- Store in a well-ventilated place. Keep container tightly closed
- Store locked up
- Keep cool.

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

None

Other information

0% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %*
ISOPROPYL ALCOHOL	67-63-0	90-100
GRAPHITE	7782-42-5	1-10
N-BUTYL ALCOHOL	71-36-3	0.1-1
1-METHYOXY-2-PROPANOL	107-98-2	0.1-1

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

First aid measures for different exposure routes

Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.
Inhalation	Move to fresh air. If breathing is difficult, give oxygen. Artificial respiration and/or oxygen may be necessary. If breathing has stopped, contact emergency medical services immediately.
Ingestion	Rinse mouth. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Drink plenty of water. Call a physician or Poison Control Center immediately.

Most important symptoms/effects, acute and delayed

Main Symptoms May cause respiratory irritation. Causes skin irritation. May be fatal if swallowed and enters airways.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media Decomposition by contact with water may generate vapors which can be ignited by heat or open flame.

Specific hazards arising from the chemical

No information available.

Explosion Data

Sensitivity to Mechanical Impact none.

Sensitivity to Static Discharge none.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES**Personal precautions, protective equipment and emergency procedures****Personal precautions**

Evacuate personnel to safe areas. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Avoid dust formation. Remove all sources of ignition. Keep people away from and upwind of spill/leak. All equipment used when handling the product must be grounded.

Environmental precautions**Environmental precautions**

Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. Should not be released into the environment.

Methods and materials for containment and cleaning up**Methods for Containment**

Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Pick up and transfer to properly labeled containers. Soak up with inert absorbent material. Clean contaminated surface thoroughly. After cleaning, flush away traces with water. Ground and bond containers when transferring material.

7. HANDLING AND STORAGE**Precautions for safe handling****Advice on safe handling**

Avoid contact with skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Keep away from open flames, hot surfaces and sources of ignition.

Conditions for safe storage, including any incompatibilities**Technical measures/Storage conditions**

Keep container tightly closed in a dry and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Keep in properly labeled containers. Keep out of the reach of children. Store locked up.

Incompatible products

Strong acids, alkalis, or oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Control parameters****Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
ISOPROPYL ALCOHOL 67-63-0	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m ³ (vacated) TWA: 400 ppm (vacated) TWA: 980 mg/m ³ (vacated) STEL: 500 ppm (vacated) STEL: 1225 mg/m ³	IDLH: 2000 ppm TWA: 400 ppm TWA: 980 mg/m ³ STEL: 500 ppm STEL: 1225 mg/m ³

GRAPHITE 7782-42-5	TWA: 2 mg/m ³ respirable fraction all forms except graphite fibers	TWA: 15 mg/m ³ total dust synthetic TWA: 5 mg/m ³ respirable fraction synthetic (vacated) TWA: 2.5 mg/m ³ respirable dust natural (vacated) TWA: 10 mg/m ³ total dust synthetic (vacated) TWA: 5 mg/m ³ respirable fraction synthetic TWA: 15 mppcf natural	IDLH: 1250 mg/m ³ TWA: 2.5 mg/m ³ natural respirable dust
N-BUTYL ALCOHOL 71-36-3	TWA: 20 ppm	TWA: 100 ppm TWA: 300 mg/m ³ (vacated) S* (vacated) Ceiling: 50 ppm (vacated) Ceiling: 150 mg/m ³	IDLH: 1400 ppm Ceiling: 50 ppm Ceiling: 150 mg/m ³
1-METHYOXY-2-PROPANOL 107-98-2	STEL: 100 ppm TWA: 50 ppm	(vacated) TWA: 100 ppm (vacated) TWA: 360 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 540 mg/m ³	TWA: 100 ppm TWA: 360 mg/m ³ STEL: 150 ppm STEL: 540 mg/m ³

ACGIH: (American Conference of Governmental Industrial Hygienists)

OSHA: (Occupational Safety & Health Administration)

NIOSH IDLH: Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Exposure controls

Engineering Measures Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

- Eye/Face Protection** Safety glasses with side-shields.
- Skin and body protection** Chemical resistant apron. Protective gloves.
- Respiratory protection** If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene measures Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and chemical properties

Physical state	Liquid	Odor	Solvent
Appearance	opaque	Odor Threshold	No information available
Color	black		
Property	Values	Remarks • Methods	
pH	No information available		
Melting/freezing point	No information available		
Boiling point/boiling range	No information available		
Flash Point	12 °C / 53.6 °F	Based on lowest flashpoint of the products constituent.	
Evaporation rate	No information available		
Flammability (solid, gas)	No information available		
Flammability Limits in Air			

upper flammability limit	No information available
lower flammability limit	No information available
Vapor pressure	No information available
Vapor density	No information available
Specific Gravity	.808
Water solubility	Practically insoluble
Partition coefficient: n-octanol/water	No information available
Autoignition temperature	No information available
Decomposition temperature	No information available
Viscosity	No information available
Explosive properties	No information available

Other information

VOC Content(%) 95.25

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to Avoid

Extremes of temperature and direct sunlight.

Incompatible Materials

Strong acids, alkalis, or oxidizing agents.

Hazardous Decomposition Products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure**Product Information**

Inhalation	Vapors may irritate throat and respiratory system. May cause drowsiness and dizziness based on components. May cause irritation of respiratory tract. Avoid breathing vapors or mists.
Eye contact	Avoid contact with eyes.
Skin contact	Irritating to skin. Repeated exposure may cause skin dryness or cracking. Prolonged skin contact may defat the skin and produce dermatitis. Avoid contact with skin.
Ingestion	May be harmful or fatal if swallowed.

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
ISOPROPYL ALCOHOL 67-63-0	= 1870 mg/kg (Rat)	= 4059 mg/kg (Rabbit)	= 72600 mg/m ³ (Rat) 4 h
N-BUTYL ALCOHOL 71-36-3	= 700 mg/kg (Rat)	= 3402 mg/kg (Rabbit)	> 8000 ppm (Rat) 4 h
1-METHOXY-2-PROPANOL 107-98-2	= 5000 mg/kg (Rat)	= 13 g/kg (Rabbit)	> 6 mg/L (Rat) 4 h

Information on toxicological effects

Symptoms Symptoms of overexposure may cause irritation to eyes or skin. May cause respiratory irritation. If swallowed may be harmful.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Irritating to skin.
Irritation Irritating to respiratory system and skin.
Sensitization None known.
Germ Cell Mutagenicity None known.
Carcinogenicity There are no known carcinogenic chemicals in this product.
Reproductive toxicity This product does not contain any known or suspected reproductive hazards.
Specific target organ systemic toxicity (single exposure) May cause respiratory irritation. May cause drowsiness and dizziness.
Specific target organ systemic toxicity (repeated exposure) None under normal use conditions.
Target Organ Effects Central nervous system, Central Vascular System (CVS), Eyes, Respiratory system, Skin.
Neurological effects Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.
Aspiration hazard Not applicable.

Numerical measures of toxicity - Product Information

Unknown Acute Toxicity 0% of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 70000 mg/kg
ATEmix (inhalation-gas) 2500000 mg/l

12. ECOLOGICAL INFORMATIONEcotoxicity

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to microorganisms	Toxicity to daphnia and other aquatic invertebrates
ISOPROPYL ALCOHOL 67-63-0	1000 mg/L EC50 Desmodemus subspicatus 96h 1000 mg/L EC50 Desmodemus subspicatus 72h	11130 mg/L LC50 Pimephales promelas 96h static 9640 mg/L LC50 Pimephales promelas 96h flow-through 1400000 µg/L LC50 Lepomis macrochirus 96h	-	13299 mg/L EC50 Daphnia magna 48h
N-BUTYL ALCOHOL 71-36-3	500 mg/L EC50 Desmodemus subspicatus 96h 500 mg/L EC50 Desmodemus subspicatus 72h	100000 - 500000 µg/L LC50 Lepomis macrochirus 96h static 1730 - 1910 mg/L LC50 Pimephales promelas 96h static 1740 mg/L LC50 Pimephales promelas 96h flow-through 1910000 µg/L LC50 Pimephales promelas 96h static	-	1897 - 2072 mg/L EC50 Daphnia magna 48h Static 1983 mg/L EC50 Daphnia magna 48h
1-METHOXY-2-PROPANO L 107-98-2	-	20.8 g/L LC50 Pimephales promelas 96h static	-	23300 mg/L EC50 Daphnia magna 48h

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical Name	log Pow
ISOPROPYL ALCOHOL 67-63-0	0.05

N-BUTYL ALCOHOL 71-36-3	0.785
1-METHYOXY-2-PROPANOL 107-98-2	-0.437

Other adverse effects No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment

Waste Disposal Methods This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

Contaminated packaging Do not re-use empty containers.

14. TRANSPORT INFORMATION

DOT Ground UN1219, ISOPROPANOL SOLUTION, 3, PGII

IATA UN1219, ISOPROPANOL SOLUTION, 3, PGII

IMDG UN1219, ISOPROPANOL SOLUTION, 3, PGII

15. REGULATORY INFORMATION

International Inventories

Chemical Name	TSCA	DSL/NDSL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	AICS
ISOPROPYL ALCOHOL	X	X	X	X	X	X	X	X
GRAPHITE	X	X	X	Not listed	X	X	X	X
N-BUTYL ALCOHOL	X	X	X	X	X	X	X	X
1-METHYOXY-2-PROPANOL	X	X	X	X	X	X	X	X

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

CHINA - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %*	SARA 313 - Threshold Values %
ISOPROPYL ALCOHOL - 67-63-0	67-63-0	90-100	1.0
N-BUTYL ALCOHOL - 71-36-3	71-36-3	0.1-1	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	no
Reactive Hazard	no

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
N-BUTYL ALCOHOL 71-36-3	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

U.S. State Regulations

California Proposition 65

This product does not contain any known Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
ISOPROPYL ALCOHOL 67-63-0	X	X	X
GRAPHITE 7782-42-5	X	X	X
N-BUTYL ALCOHOL 71-36-3	X	X	X
1-METHYOXY-2-PROPANOL 107-98-2	X	X	X

EPA Pesticide Registration Number Not applicable

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

16. OTHER INFORMATION

NFPA	Health Hazard 2	Flammability 4	Instability 0	Physical and chemical hazards -
HMS	Health Hazard 2	Flammability 4	Physical Hazard 1	Personal protection B

Prepared By IES
30241 Commerce Drive
San Antonio, FL 33576

Issuing date 08-Jun-2015
Revision Date 08-Jun-2015

Revision Note
No information available

Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet