

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

MAR CALACATTA

TECHNICAL CHARACTERISTICS

Available Formats:	24x24, 12x24 & 3x24 Bullnose		
Style Description:	Marble	Glaze Application Method:	HDIT Inkjet
Visual Characteristics:	Calacatta	Number of Faces/Screens:	N/A
Thickness in mm:	10.85	Number of Punches/Molds:	N/A
Modular Suitability:	Yes	Body Type:	Porcelain (<.5%)
Application:	Residential/Commercial	Color Body Unglazed:	No
Recycled Content: Post or Pre Customer	N/A	Surface Type:	Polished
Rectified:	Yes	Recommended Grout Joint:	No less than 1/8"

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	< .5%	Static COF:	Wet: 0.58 Dry: 0.63
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	N/A
Scratch Hardness (MOHS)	N/A	Breaking Strength:	2370N (34N/mm ²)
Frost Resistant:	Yes	Thermal Shock Resistance:	Yes
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm ² :	Passes
Chemical Resistance:	Yes		

PACKING INFORMATION - 24x24 *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	10.98	Pieces per Carton:	3
SqFt per Pallet:	395.28	Pounds per SqFt:	4.91 Lbs
Boxes per Pallet:	36	SqFt per Container:	N/A
Pallets per Container:	N/A		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".