

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME

Nairobi

## TECHNICAL CHARACTERISTICS

Available Formats:	20x20		
Style Description:	Onyx Marble Look	Glaze Application Method:	H.D.I.T. Inkjet
Visual Characteristics:		Number of Faces/Screens:	3
Thickness in mm:	9.1	Number of Punches/Molds:	1
Modular Suitability:	Yes	Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	
Recycled Content: Post or Pre Customer		Surface Type:	
Rectified:	No	Recommended Grout Joint:	TCNA

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	<0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	0.45
Scratch Hardness (MOHS)	6	Breaking Strength:	Passes
Frost Resistant:	Yes	Thermal Shock Resistance:	Yes
PEI/Abrasion Resistance:	III	Deep Abrasion Test <175mm <sup>2</sup> :	
Chemical Resistance:	Yes		

## PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	13.46	Pieces per Carton:	5
SqFt per Pallet:	441.18	Pounds per Carton:	
Boxes per Pallet:	33	SqFt per Container:	
Pallets per Container:	31		

### Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".