

Drive Belt Dimension Chart

BELT P/N	LENGTH	WIDTH
0227-011	44.000 ± .188 inch	1.250 inch
0227-014	45.500 ± .188 inch	1.250 inch
0227-016	45.063 ± .188 inch	1.250 inch
0227-019	43.250 ± .188 inch	1.250 inch
0227-020	46.688 ± .188 inch	1.250 inch
0227-030	43.500 ± .188 inch	1.375 inch
0227-100	45.500 ± .188 inch	1.375 inch
0227-103	43.625 ± .125 inch	1.375 inch
*0627-002	43.625 ± .188 inch	1.375 inch
*0627-004	43.625 ± .188 inch	1.375 inch
*0627-006	43.625 ± .188 inch	1.375 inch
*0627-010	47.750 ± .188 inch	1.375 inch
*0627-011	45.750 ± .188 inch	1.375 inch
*0627-012	47.750 ± .188 inch	1.375 inch
0627-013	49.000 ± .188 inch	1.437 inch
0627-014	49.000 ± .188 inch	1.437 inch
*0627-020	48.071 ± .188 inch	1.406 inch
*0627-021	47.750 ± .188 inch	1.385 inch
*0627-031	47.750 ± .178 inch	1.382 inch
*0627-032	44.570 ± .178 inch	1.448 inch
*0627-033	50.285 ± .188 inch	1.437 inch
*0627-034	44.024 ± .178 inch	1.448 inch
*0627-035	47.750 ± .178 inch	1.400 inch
*0627-036	45.024 ± .178 inch	1.448 inch
*0627-044	44.706 ± .178 inch	1.448 inch

BELT P/N	LENGTH	WIDTH
*0627-045	45.223 ± .178 inch	1.448 inch
*0627-046	45.998 ± .178 inch	1.448 inch
*0627-047	43.547 ± .178 inch	1.448 inch
*0627-048	46.986 ± .178 inch	1.448 inch
*0627-049	48.162 ± .178 inch	1.448 inch
*0627-059	48.162 ± .178 inch	1.448 inch
**0627-060	45.998 ± .178 inch	1.448 inch
*0627-067	45.394 ± .178 inch	1.406 inch
*0627-069	42.953 ± .178 inch	1.406 inch
*0627-070	44.250 ± .178 inch	1.448 inch
**0627-060	45.998 ± .178 inch	1.448 inch
*0627-067	45.394 ± .178 inch	1.406 inch
**0627-060	45.998 ± .178 inch	1.448 inch
*0627-067	45.394 ± .178 inch	1.406 inch
*0627-069	42.953 ± .178 inch	1.406 inch
*0627-070	44.250 ± .178 inch	1.448 inch
***0627-073	43.547 ± .178 inch	1.448 inch
**0627-075	44.250 ± .178 inch	1.448 inch
**0627-076	43.547 ± .178 inch	1.448 inch
*0627-081	46.378 ± .178 inch	1.448 inch
***0627-082	46.259 ± .178 inch	1.448 inch
**0627-083	47.519 ± .178 inch	1.448 inch
***0627-084	47.519 ± .178 inch	1.448 inch
***0627-085	48.149 ± .178 inch	1.448 inch
***0627-086	48.149 ± .178 inch	1.448 inch

*High Performance **Improved Compression Resistance; Improved Heat Resistance ***Best Compression Resistance; Best Heat Resistance

■ **NOTE: The difference between a * drive belt and a ** drive belt of the same dimension is hardness. A ** drive belt is more flexible and if used in place of a * drive belt, the engine will run at a lower RPM.**