

P***D******Q*** **MONO**

PRICE DELIVERY QUALITY

YOU
CAN'T...

BUILD IT FOR THIS!


P **PRICE**

\$40,270

BUILD IT THIS FAST!

D **DELIVERY**

Stock to 6 Weeks



BUILD IT THIS WELL!

Q **QUALITY**

SPECIFICATIONS

Base Design

Voltage Input:	480 VAC, 3-Phase
Total Heat Zones:	BASE CONFIGURATION: 480V Single Phase 5) Barrel Zones (30A) with cooling 4) Other Zones (30A) heat only 6) Die Zones (30A) heat only
Melt Pressure:	Reading Input with Calibration
Melt Temperature:	Reading
Additional Starters:	2 (Oil and Water Pumps)
Die Plugs:	6 Hubbell Receptacles with Disconnects
Primary Nip:	3 Hp Yaskawa AC Drive with Encoder Feedback
Touch Screen:	15" Color Touch-Screen Mounted on the Door

Options

5-10HP Primary Drive
Secondary Drive up to 10HP
Arc-Flash (Required with 480V/240V systems)
Swing Arm

Tower Lights/Buzzer
2 Additional Die Plugs
All 240V Zones / 240V Die Zones
480 V Three Phase Barrel

Features

Easy-to-Use Graphical Display of the Process
Remote Connectivity and Support
Recipe Control with Scheduler
Customizable Security Access
Temperature Control:

- Auto-Tune PID
- Extruder Preheat
- Soak Feature
- Broken Probe Alarm
- Open Heater Alarm
- Shorted Solid-State Relay Alarm
- High-Low Temperature Alarm (Indicated by Text Color and Flag)

Protective Features

- Cold Zone Start Inhibit
- Runaway Heat Warning and Shutdown
- High Pressure Shutdown

Data Collection (stored in a .CSV file format)

- Process Data
- Alarm Log
- Maintenance Log
- Trending Screen



(972) 906-7445
Give Us a Call!

www.integratedcontroltech.com

