

BOVIE® BANTAM | PRO ELECTROSURGICAL GENERATOR



The Bovie® Bantam PRO A952 is a high frequency desiccator that also has cutting ability. The unit provides 50 watts of cutting power and coagulation modes – plenty of power for most procedures performed in the doctor's office. Power is adjustable in 1/10th watt increments from 0 to 10 watts, for the most accurate output available. No grounding pad is required when working in desiccation mode.

The unit also features NEM™ (Neutral Electrode Monitoring) pad sensing technology which monitors the return electrode for optimum patient protection. The Bovie® Bantam PRO A952 is backed by Bovie's four (4) year manufacturer's warranty.

BOVIE® BANTAM | PRO ELECTROSURGICAL GENERATOR

PRODUCTS INCLUDED

 <p>A952</p>	
 <p>A902</p>	 <p>A804, A805, A806, A807, A806DE, A807DE</p>
 <p>ES01, ES02, ES20</p>	 <p>A837</p>
 <p>A910</p>	 <p>A910ST</p>

Style # A952

▼ Products Included

- A952** (1) electrosurgical generator
- A902** (1) handpiece
- A804** (5) non-sterile sharp dermal tips
- A805** (2) sterile sharp dermal tips
- A806** (5) non-sterile blunt dermal tips
- A807** (2) sterile blunt dermal tips
- A806DE** (2) non-sterile DERM-Elite™ Premium blunt dermal tips
- A807DE** (2) sterile DERM-Elite Premium blunt dermal tips
- ES01** (3) blade sterile disposable electrodes
- ES02** (1) needle sterile disposable electrodes
- ES20** (1) ball sterile disposable electrodes
- A910** (2) non-sterile disposable handpiece sheaths
- A910ST** (2) sterile disposable handpiece sheaths
- A1252C** (2) reusable grounding cord*
- ESRE** (5) disposable split grounding pads*
- A837** (1) wall mount kit

110 VAC Hospital-grade power cord*

User's guide (MC-55-238-001)*

Dimensions

Height: 188 mm (7.40 in.)
 Width: 228 mm (8.98 in.)
 Depth: 105 mm (4.13 in.)
 Weight: < 2.26 kg (< 5 lbs.)

Output Power

Cut: 50 watts
 Blend: 50 watts
 Coagulation: 50 watts
 Fulguration: 40 watts
 Bipolar: 40 watts
 Micro Bipolar: 40 watts

Output Frequency: 304-451 kHz

Line Frequency: 50-60 Hz

Line Voltage: 100-240 VAC

Warranty: **FOUR YEARS**