



**NOTES:**

1. MOUNTING ANGLE
2. EXTRUDED ALUMINUM FASCIA
3. 2 5/8" EXTRUDED ALUMINUM CLOSURE
4. EXTRUDED ALUMINUM EXTERIOR HEMBAR
5. 2"  $\phi$  EXTRUDED ALUMINUM TUBE
6. ALUMINUM END BRACKETS
7. FABRIC: 1%, 3%, 5%, 10% OPENNESS OR BLACKOUT
8. MOTORIZED BLACKOUT SIDE CHANNEL
9. MANUAL BLACKOUT BOTTOM CHANNEL

**\*\* NOTE \*\***

JUNCTION BOX TO BE LOCATED WITHIN 3 FT OF MOTOR LOCATION. MOTOR LOCATION TO BE DETERMINED WITH SOLARFECTIVE REPRESENTATIVE.

**Solarfective**

55 Hymus Road, Scarborough  
Ontario, Canada. M1L 2C6

Tel. (416) 421-3800  
Fax. (416) 421-8424

Web Site: [www.solarfective.com](http://www.solarfective.com)  
Email: [shades@solarfective.com](mailto:shades@solarfective.com)

MOTORIZED SHADE WITH CEILING MOUNT 4" FASCIA  
SIDE AND BOTTOM CHANNELS

PROJECT: —

DATE:  
JAN. 01, 2015

SCALE:  
N.T.S.

FILE No.  
—

DRAWN:  
ADIE

DWG. No.  
RD-17

REV  
0