

Cold Water Gasoline Direct Drive

The powerful gasoline direct drive JP Series is designed for excellent balance and mobility, and is highly recommended for industrial jobs.

To see more online, scan here or go to www.mitm.com:



Pump

- Forged brass manifold
- Thermal relief valve
- In-line water strainer

Frame

- Powder coated steel frame and base plate with 1¼-inch tube handles
- Flat-free tires


Unit Includes:

- 50-foot x ¾-inch non-marking hose with quick connects
- Insulated trigger gun with safety lock-off



JP-2703-3MSB

Limited Warranties:

1 Year Mi-T-M Unloader	7 Year Pump
3 Year Honda Engine	
5 Year Subaru Engine	Intertek Certified to UL-1776

MODEL NUMBER	PSI	GPM	DISPLACEMENT/ENGINE	PUMP	Mi-T-M NO.	UNLOADER	NOZZLES	LANCE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
JP-2403-3MHB	2400	2.4	196cc Honda OHV	Mi-T-M	3-0353	Mi-T-M, adjustable pressure	0°, 15° & 25°	36in.	37x21x24.5in.	100 lb.	75 lb.
JP-2403-3MSB	2400	2.4	211cc Subaru OHC	Mi-T-M	3-0353	Mi-T-M, adjustable pressure	0°, 15° & 25°	36in.	37x21x24.5in.	100 lb.	75 lb.
JP-2703-3MHB	2700	2.4	196cc Honda OHV	Mi-T-M	3-0353	Mi-T-M, adjustable pressure	0°, 15° & 25°	36in.	37x21x24.5in.	110 lb.	85 lb.
JP-2703-3MSB	2700	2.4	211cc Subaru OHC	Mi-T-M	3-0353	Mi-T-M, adjustable pressure	0°, 15° & 25°	36in.	37x21x24.5in.	110 lb.	85 lb.
JP-3003-3MHB	3000	3.0	270cc Honda OHV	AR	3-0389	Mi-T-M, adjustable pressure	0°, 15° & 25°	36in.	40x22.5x24.5in.	180 lb.	130 lb.
JP-3003-3MSB	3000	3.0	265cc Subaru OHC	AR	3-0389	Mi-T-M, adjustable pressure	0°, 15° & 25°	36in.	40x22.5x24.5in.	180 lb.	130 lb.
JP-3504-3MHB	3500	3.5	389cc Honda OHV	AR	3-0310	Mi-T-M, adjustable pressure	0°, 15° & 25°	48in.	40x22.5x24.5in.	192 lb.	142 lb.
JP-3504-3MSB	3500	3.5	404cc Subaru OHC	AR	3-0310	Mi-T-M, adjustable pressure	0°, 15° & 25°	48in.	40x22.5x24.5in.	192 lb.	142 lb.
JP-4004-3MHB	4000	3.5	389cc Honda OHV	AR	3-0310	Mi-T-M, adjustable pressure	0°, 15° & 25°	48in.	40x22.5x24.5in.	192 lb.	142 lb.
JP-4004-3MSB	4000	3.5	404cc Subaru OHC	AR	3-0310	Mi-T-M, adjustable pressure	0°, 15° & 25°	48in.	40x22.5x24.5in.	192 lb.	142 lb.

Accessories & Options:

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
50-0161	High pressure detergent injector	All models	CX-0005	48-in. insulated dual lance	All models
851-0338	50-ft. x ¾-in. non-marking hose	All models	CX-0083	External bypass system	2400 to 2700-PSI models
AW-8400-0021	Low pressure detergent injector	All models	CX-0084	External bypass system	3500 to 4000-PSI models