

HW19AC80S-C



2.0MP 4in1 IR Bullet Camera

Features

- > Full HD resolution 1920 x 1080P
- > Minimum illumination : 0.01Lux(AGC ON), 0Lux IR on
- > Support AHD/TVI/CVI/CVBS 4in1 signal

- > Video output: TVI/AHD/CVI(1080P) & CVBS 960H can be switched freely by OSD
- > OSP antioxidant PCB, power/video dual lightning protection design
- > OSD menu control up the coaxial cable (UTC)
- > Day/Night (ICR), AWB, AGC, BLC, 2D/3D-DNR
- > Motion Detection, Privacy Mask, Mirror
- > 18pcs small IR array, IR distance 20 meters
- > Fixed focal lens 3.6/6mm
- > IP66

Technical Specifications

Model	HW19AC80S-C
Camera	
Image Sensor	1/2.9" 2.07 Mega pixels Sony CMOS
Effective Pixel	1920(H) x 1080 (V)
Video Resolution	1080P@25/30fps
Electronic Shutter	AUTO, 1/50(60)-1/50,000sec
System	PAL/NTSC
Min. Illumination	0.01Lux(AGC ON), 0Lux IR on
Video Output	Support AHD/TVI/CVI/CVBS 4in1 signal
Day/Night	Auto/Color/(B/W)/EXT (OSD switch)
S/N Ratio	≥41dB
White Balance	Auto
WDR	Digital WDR
AGC/BLC	Support

4IN1 Camera Datasheet

DNR	2D/3DDNR, multi-levels adjustable
OSD Menu	Multi languages OSD menu control up the coaxial cable (UTC)
Language	English/ Simplified Chinese/Traditional Chinese /German/French/ Italian/ Spanish/ Polish/ Russian/ Portuguese/ Dutch/ Turkish
Other	Defog, Motion Detection, Privacy Mask, Mirror, Flip
IR Led	18pcs IR array led
IR Distance	20m
Lens	
Focal length	Fixed focal lens 3.6/6mm@F2.1/F2, M12
General	
Power Supply	DC12V±10%
Power Consumption	0.72W/2.64W(IR ON)
Operating Environment	-20°C ~ +60°C Humidity less than95%(Non-condensing)
Dimensions(mm)	172mm× ϕ 65.7×62.7mm
Weight	0.32KG

Dimensions (mm)

