

STEALTH Series

A024_1017

Booth filters & tool savers



STEALTH 6950B & STEALTH 6900B

For use with air tools, sand blasting, sanding impacts, buffing; Ideal for mechanical section of body shop:

STEALTH 6900B No Regulator

STEALTH 6950B 1/4" Regulator

Replacement Element: 6950-1



STEALTH 7000B & STEALTH 7030B

Perfect after-filters for desiccant dryers and as final paint air filter & control unit:

STEALTH 1000B 1/2" Regulator

STEALTH 1500B 1/2" Regulator & multiport manifold

STEALTH 7000B 1/4" Regulator

STEALTH 7030B 3/8" Regulator

STEALTH 7800B No Regulator

Replacement Element: 3C-060



STEALTH 6060B

Ideal for paint booths, lacquer spraying, prep stations and protecting critical air tools:

STEALTH 6060B 3/8" Regulator

1st Stage Replacement Element: 6960-1

2nd Stage Replacement Element: 3C-060



(800) 521-9200



www.driair.com | www.rti-pbe.com



@RTIPBE



@rti_pbe



Removes: ● ●

1.0 micron • 60 SCFM • Brass Manual Petcock Drain

**1/4"**
STEALTH 6900B
STEALTH 6950B
STEALTH 6952B

 No Regulator
 Regulator w/ Gauge
 Regulator w/ Gauge, (2) 1/4" Outlets
3/8"
STEALTH 3050B
STEALTH 3052B

 Regulator w/ Gauge
 Regulator w/ Gauge, (2) 3/8" Outlets

Replacement Element: 6950-1

Removes: ● ● ●

1.0 micron • 60 SCFM • Brass Manual Petcock Drain

**1/4"**
STEALTH 6910B
STEALTH 6960B
STEALTH 6962B

 No Regulator
 Regulator w/ Gauge
 Regulator w/ Gauge, (2) 1/4" Outlets
3/8"
STEALTH 3060B
STEALTH 3062B

 Regulator w/ Gauge
 Regulator w/ Gauge, (2) 3/8" Outlets

Replacement Element: 6960-1

Removes: ●

0.01 micron • 60 SCFM • Brass Manual Petcock Drain

**1/4"**
STEALTH 7000B
STEALTH 7800B

 Regulator w/ Gauge
 No Regulator
1/2"
STEALTH 1000B
STEALTH 1500B

 Regulator w/ Gauge
 Regulator w/ Gauge and manifold
3/8"**STEALTH 7030B**

Regulator w/ Gauge

Replacement Element: 3C-060

Removes: ● ● ●

 0.01 micron • 60 SCFM • 1st Stage: Automatic Float Drain
 2nd Stage: Brass Manual Petcock Drain
**3/8"****STEALTH 6060B**

Regulator w/ Gauge

 1st Stage Replacement Element: 6960-1
 2nd Stage Replacement Element: 3C-060

Note: All Stealth units feature 1/2" NPT Inlet, Max Pressure: 200 PSI, Max Temp: 125°F | Removal Key: ● Water ● Dirt ● Oil



(800) 521-9200



www.driair.com | www.rti-pbe.com



@RTiPBE



@rti_pbe

