



Industrial Butyl-Free

CLEANER AND DEGREASER
PRODUCT NO.: WH-410

- Industrial & Commercial Use
- High Power Cleaner/Degreaser
- Phosphate-Free
- Versatile & Cost Effective
- Biodegradable/EPA VOC Compliant
- USDA Classifications: A-1, C-1
- Alkylphenol Ethoxylate (APE) Free

WH-410 INDUSTRIAL BUTYL-FREE is a water-based cleaner/degreaser formulated for demanding uses. It is recommended for cleaning shop floors, machinery and heavy equipment such as excavators, bulldozers, backhoes, dump trucks, and more. Strong enough to tackle hard-to-clean surfaces. Exceptional worker safety and environmental profile.

Applications & Uses	Dilutions	Directions
Shop Floors	Full Strength 1:1 10:1 30:1	Use full strength or dilute 1:1 to "Shock Clean" floor surfaces. For regular maintenance cleaning, dilute 10:1. For light maintenance, dilute 30:1. Dilute product, apply to floor surface, allow several minutes contact time, scrub floors in usual manner, and rinse with clean water.
Agitation Machinery	20:1	Operate machinery according to the manufacturer's directions for use.
Axles, Engines, Chassis, Auto Parts, Tools	5:1	Dilute product, apply to surface, allow several minutes contact time, and wipe or rinse with clean water.
Machinery and Equipment	5:1	Dilute product, apply to surface, allow several minutes contact time, brush, and wipe or rinse clean with water.
Metal Preparation Prior to Painting	Full Strength 1:1	Use full strength or dilute 1:1 to "Shock Clean" surface. Apply product, allow several minutes contact time, brush, or hot water high-pressure rinse clean. Cleaning metal surfaces in this manner results in a chemically clean surface that is in excellent condition for priming or painting.
Pressure Washing	3:1 10:1	As a pretreatment, dilute product 3:1, apply to surface, allow 3 minutes contact time, and high pressure rinse clean. As a pressure wash, dilute product 10:1 and operate machinery according to the manufacturer's directions for use.
Steam Cleaning	20:1	Operate machinery according to the manufacturer's directions for use.
Tires	5:1	Dilute product, apply to tire surface, allow several minutes contact time, brush, and rinse with clean water.
Plastic or Vinyl	30:1	Dilute product, apply to surface, and wipe or rinse with clean water.

Suggested Industry Applications:

Aeronautical
Automotive Dealerships
Construction
Farming Equipment
Fleet Operations

Heavy Industry
Rail
Service Stations & Machine Shops
Shipping
Steel Manufacturing

Waste Management
Highway Maintenance
Mining
Oil Refineries
Pulp & Paper Production

Specifications:

Appearance	Clear, Slight Red Liquid
Odor	Mild, cherry scented
pH	> 13
Flashpoint	> 200°F
%VOC	< 3%
DOT Label	Corrosive

General Cautions For Use:

Use this product on painted or glass surfaces in highly diluted form only and rinse thoroughly.
As with all cleaning agents, keep this product out of the reach of children.
As with most cleaning agents, this product should NOT be allowed to dry on surfaces.
Dilutions are recommendations only, as you become familiar with the product's performance, adjust accordingly.

Container Sizes:

4/1 Gallon Case
5 Gallon Pail
55 Gallon Drum
275 Gallon Totes Available on Request

Manufactured for WorkHorse Cleaner Products - P.O. Box 1086, Fairhope, AL 36533

Call Toll Free: 844-964-6444 or (251) 510-3614 for additional product information, or visit: www.workhorsecleaners.com