



Price list (UL&DLC Listed IP68 LED Tri-proof Light)

| Picture | Item Code | Dimension (mm) | Power | LED Q'ty (CRI>80) | Input Voltage | Power Factor | Efficacy (Lm/W) | Luminous (LM) | Certificate | Lifespan | UL standard driver | | CCT |
|--|---------------|-----------------|-------|-------------------|---------------|--------------|-----------------|---------------|-------------|----------|--------------------|--|----------------------------------|
| | | | | | | | | | | | UNIT PRICE | Lux distance curve(lux) | |
| | | | | | | | | | | | 120 BEAM ANGLE | | |
|  | SL-P68X2-20-X | 24.01 x 3.94 in | 20W | 120 | AC100-277V | >0.95 | 100~120 | 2000~2400 | N/A | 50K hrs | CALL |  <p>Height E Diameter</p> | 3000K 4000K 5000K 6000K |
| | SL-P68X2-30-X | 24.01 x 3.94 in | 30W | 192 | AC100-277V | >0.95 | 100~120 | 3000~3600 | N/A | 50K hrs | CALL | | |
| | SL-P68X4-40-X | 47.91 x 3.94 in | 40W | 240 | AC100-277V | >0.95 | 100~120 | 4000~4800 | UL cUL DLC | 50K hrs | CALL | | |
| | SL-P68X4-50-X | 47.91 x 3.94 in | 50W | 288 | AC100-277V | >0.95 | 100~120 | 5000~6000 | UL cUL DLC | 50K hrs | CALL | | |
| | SL-P68X5-50-X | 59.72 x 3.94 in | 50W | 336 | AC100-277V | >0.95 | 100~120 | 5000~6000 | N/A | 50K hrs | CALL | | |
| | SL-P68X5-60-X | 59.72 x 3.94 in | 60W | 384 | AC100-277V | >0.95 | 100~120 | 6000~7200 | UL cUL DLC | 50K hrs | CALL | | |

Price list (Emergency IP68 LED Tri-proof Light)

| Emergency 3 hours | | | | | | | | | | | | | |
|--|---------------|-----------------|-------|-------------------|--------------------------|--------------|-----------------|---------------|-------------|----------|--------------------|--|----------------------------------|
| Picture | Item Code | Dimension (mm) | Power | LED Q'ty (CRI>80) | Input Voltage | Power Factor | Efficacy (Lm/W) | Luminous (LM) | Certificate | Lifespan | UL standard driver | | CCT |
| | | | | | | | | | | | UNIT PRICE | Lux distance curve(lux) | |
| | | | | | | | | | | | 120 BEAM ANGLE | | |
|  | SL-P68X2-20-X | 24.01 x 3.94 in | 20W | 120 | AC100-240V AC100-277V | >0.95 | 100~120 | 2000~2400 | N/A | 30K hrs | CALL |  <p>Height E Diameter</p> | 3000K 4000K 5000K 6000K |
| | SL-P68X2-30-X | 24.01 x 3.94 in | 30W | 192 | AC100-240V AC100-277V | >0.95 | 100~120 | 3000~3600 | N/A | 30K hrs | CALL | | |
| | SL-P68X4-40-X | 47.91 x 3.94 in | 40W | 240 | AC100-240V AC100-277V | >0.95 | 100~120 | 4000~4800 | N/A | 30K hrs | CALL | | |
| | SL-P68X4-50-X | 47.91 x 3.94 in | 50W | 288 | AC100-240V AC100-277V | >0.95 | 100~120 | 5000~6000 | N/A | 30K hrs | CALL | | |
| | SL-P68X5-50-X | 59.72 x 3.94 in | 50W | 336 | AC100-240V AC100-277V | >0.95 | 100~120 | 5000~6000 | N/A | 30K hrs | CALL | | |
| | SL-P68X5-60-X | 59.72 x 3.94 in | 60W | 384 | AC100-240V AC100-277V | >0.95 | 100~120 | 6000~7200 | N/A | 30K hrs | CALL | | |