

## Equiplite Spinnaker Blocks



**NEW:** all the blocks with UV cover for fully UV protection for long life

**These Spinnaker blocks are similar in design to Equiplite snatch blocks. They employ wide Acetyl or aluminium sheaves to pass two sheets. The spinnaker blocks can be used for double sheets.**

Note: Dyneema cover are coated with UV coatings, exposure and wear due to usage however will reduce strength. It is recommended that Loops should be replaced every three years under normal usage. In sizing for heavy use, SWL should be conservative.

**All data approx and subject to change without notice .  
Other sizes available on special order.**

**Unspecified dims. mm.  
Break Load approx. 1.8 to 2 x SWL.**

Part	*Sheave Ø is approx.		*Other throats available		
	Sheave Ø	2 X Max Sheets (mm)	Throat (mm)	SWL (Kg)	Weight (Gm)
64-80-12 HL SpB	80	2 X 22	87	14.000	950
64-80-12 LL SpB	80	2 X 22	87	8.000	950
54-74-10 HL SpB	74	2 X 18	80	9.000	600
54-74-10 LL SpB	74	2 X 18	80	5.500	550
46-65-8 HL SpB	65	2 X 16	60	6.000	410
46-65-8 LL SpB	65	2 X 16	60	4.000	410
36-55-6 HL SpB	55	2 X 14	45	4.000	290
36-55-6 LL SpB	55	2 X 14	45	3.000	290
30-46-5 HL SpB	46	2 X 14	37	3.000	175
30-46-5 LL SpB	46	2 X 14	37	2.200	175
25-43-5 HL SpB	43	2 X 12	36	3.000	170
25-43-5 LL SpB	43	2 X 12	36	2.200	170
20-42-4 HL SpB	42	2 X 10	32	2.200	85
20-42-4 LL SpB	42	2 X 10	32	1.500	85

Above **HL**= Hi Load version employing hi load low friction polymer.

All details approximate.

Roller bearings and other types available special order.