

Material Safety Data Sheet (MSDS)

Chain & Cable Lube

MATERIAL SAFETY DATA SHEET

Effective Date: 6-6-02

Revision Date: none

Chain & Cable Lube

Code: SD

Page: 1

Section 1 - Product and Company Identification

PRODUCT NAME: Chain & Cable Lube

MANUFACTURER'S NAME:

Specialty Division, Sprayon Products
26300 Fargo Avenue
Bedford Heights, OH 44146
(800) 832-2541

EMERGENCY TELEPHONE NUMBER
(216) 566-2917

MISCELLANEOUS INFORMATION

Section 2 - Hazardous Ingredients

% by WT	CAS No.	INGREDIENT	UNITS	VAPOR PRESSURE
14	74-98-6	Propane		
ACGIH TLV	2500	ppm	760	mm
OSHA PEL	1000	ppm		
6	106-97-8	Butane		
ACGIH TLV	800	ppm	760	mm
OSHA PEL	800	ppm		
43	64742-52-5	Heavy Naphthenic Petroleum Oil.		
ACGIH TLV	5	mg/m3 as Mist		
OSHA PEL	5	mg/m3 as Mist		
36	64742-62-7	Paraffin Oil.		
ACGIH TLV	5	mg/m3 as Mist		
OSHA PEL	5	mg/m3 as Mist		

Section 3 - Hazards Identification

ROUTES OF EXPOSURE

Exposure may be by INHALATION and/or SKIN or EYE contact, depending on conditions of use. To minimize exposure, follow recommendations for proper use, ventilation, and personal protective equipment.

EFFECTS OF OVEREXPOSURE

Irritation of eyes, skin and upper respiratory system.

May cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists.

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

None generally recognized.

CANCER INFORMATION

For complete discussion of toxicology data refer to Section 11.

MATERIAL SAFETY DATA SHEET

Effective Date: 6-6-02

Revision Date: none

Chain & Cable Lube

Code: SD

Page: 2

=====
Section 4 - First Aid Measures

If INHALED: If affected, remove from exposure. Restore breathing.

Keep warm and quiet.

If on SKIN: Wash affected area thoroughly with soap and water.

Remove contaminated clothing and launder before re-use.

If in EYES: Flush eyes with large amounts of water for 15 minutes.

Get medical attention.

If SWALLOWED: Do not induce vomiting.

Get medical attention immediately.

=====
Section 5 - Firefighting Measures

FLASH POINT LEL UEL

Propellant < 0 F 1.9 9.5

EXTINGUISHING MEDIA

Carbon Dioxide, Dry Chemical, Foam

UNUSUAL FIRE AND EXPLOSION HAZARDS

Containers may explode when exposed to extreme heat.

Application to hot surfaces requires special precautions.

During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

SPECIAL FIRE FIGHTING PROCEDURES

Full protective equipment including self-contained breathing apparatus should be used.

Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

=====
Section 6 - Environmental Release Measures

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Remove all sources of ignition. Ventilate the area.

Remove with inert absorbent.

=====
MATERIAL SAFETY DATA SHEET

Effective Date: 6-6-02

Revision Date: none

Chain & Cable Lube

Code: SD

Page: 3

=====
Section 7 - Handling and Storage

STORAGE CATEGORY

NFPA 30B Level 3 Aerosol

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Keep away from heat, sparks, and open flame. Vapors will accumulate readily and may ignite explosively.

During use and until all vapors are gone: Keep area ventilated - Do not smoke - Extinguish all flames, pilot lights, and heaters - Turn off stoves, electric tools and appliances, and any other sources of ignition.

Consult NFPA Code. Use approved Bonding and Grounding procedures. Contents under pressure. Do not puncture, incinerate, or expose to temperature above 120F. Heat from sunlight, radiators, stoves, hot water, and other heat sources could cause container to burst. Do not take internally. Keep out of the reach of children.

Section 8 - Exposure Controls/Personal Protection

PRECAUTIONS TO BE TAKEN IN USE

Use only with adequate ventilation.
Avoid contact with skin and eyes. Avoid breathing vapor and spray mist.
Wash hands after using.

VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

PROTECTIVE GLOVES

None required for normal application of aerosol products where minimal skin contact is expected. For long or repeated contact, wear chemical resistant gloves.

EYE PROTECTION

Wear safety spectacles with unperforated sideshields.

OTHER PRECAUTIONS

Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

MATERIAL SAFETY DATA SHEET

Effective Date: 6-6-02

Revision Date: none

Chain & Cable Lube

Code: SD

Page: 4

Section 9 - Physical and Chemical Properties

PRODUCT WEIGHT	6.63 lb/gal	794 g/l
SPECIFIC GRAVITY	0.80	
BOILING POINT	<0 - 34 F	<-18 - 1 C
MELTING POINT	Not Available	
VOLATILE VOLUME	30 %	
EVAPORATION RATE	Faster than ether	
VAPOR DENSITY	Heavier than air	
SOLUBILITY IN WATER	N.A.	
VOLATILE ORGANIC COMPOUNDS (VOC Theoretical)		
Volatile Weight 20.00 % Less Federally Exempt Solvents		

Section 10 - Stability and Reactivity

STABILITY -- Stable

CONDITIONS TO AVOID

None known.

INCOMPATIBILITY

None known.

HAZARDOUS DECOMPOSITION PRODUCTS

By fire: Carbon Dioxide, Carbon Monoxide

No ingredients in this product are subject to SARA 313 (40 CFR 372.65C) Supplier Notification.

CALIFORNIA PROPOSITION 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

TSCA CERTIFICATION

All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

=====
Section 16 - Other Information

This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.