

The Magic is the Media

A ISO 9001:2008 - ANSI-ISO-ASQ Q9001-2008 Company

SECTION I

PRODUCT NAME OR NUMBER (as it appears on label)			
Magic Aerospace WheelBlast® Plastic Abrasive			
MANUFACTURER'S NAME	EMERGENCY TELEPHONE		
U. S. Technology Media Inc.	NO. (330) 455-1181		
ADDRESS (Number, Street, City and Zip Code) DATE PREPARED/REVISED			
509 Water ST., Bolivar OH. 44612	- NO. 02/19/2025		
MATERIAL DESCRIPTION, PROPER SHIPPING NAME: Abrasive			
HAZARD CLASSES (as applicable):			
CHEMICAL FAMILY: Various	FORMULA: N.A.		

SECTION II – INGREDIENTS

(list all ingredients)

CAS REG ISTR Y NO.	Approx. %W	Chemical Name(s)	OSHA PEL	ACGIH TLV	Other Limits Recommended
9003-08-1 9011-05-6 9004-34-6 1318-93-0	>1%	Polymerized Urea-Melamine Formaldehyde Compound w/Alpha Cellulose Filler and Montmorillonite Clay			
25852-37-3	>1%	Acrylate Polymer – Polymerized and Cross-linked			
2764-13-8	<1%	Anti-Static Agent – Cal Stat 600			
5280-80-8 13463-67-7 12769-96-9	<1%	Pigments and Additives			

Material is a blend of thermoset and thermoplastic plastic.

SECTION III – PHYSICAL DATA

BOILING POINT°F°C	SPECIFIC GRAVITY (H ₂ O=1):	
N.A.	1.36-1.46	
MELTING POINT°F°C	PERCENT VOLATILE BY	PERCENT SOLID BY WEIGHT
N.A.	VOLUME (%) N.A.	(%) 100
VAPOR DENSITY (AIR=1) N.A.	EVAPORATION RATE (=1) N.A.	
SOLUBILITY IN WATER: N.A.	pH = 4-8	
APPEARANCE AND ODOR: Mult	MATERIAL FORM: Solid	
odor		

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT °F _	ºC N.A.	FLAMMABLE: N.A.	LEL: N.A.	UEL: N.A.
EXTINGUISHING MEDIA: Carbon dioxide, dry chemicals or water fog				
SPECIAL FIRE FIGHTING PROCEDURES: None				
UNUSUAL FIRE AND EXPLOSION HAZARDS: None				

SECTION V – HEALTH HAZARD DATA

		SURE – Conditions to a	void:	THRESHOLD LIMIT VALUE:
		nd/or skin can occur.		PERMISSIBLE EXPOSURE LIMIT:
		TRY: 🗹 Inhalation		in Contact
				ust – cross exposure can irritate respiratory tract.
			ould be d	consulted. Prolonged exposure to lead chromate
could lead to increa				O DI O O I OOHA Dawalata 10 V
CARCINOGENICI	IY: NIP	PD, Cr, Ca IARC MOI	nograpr	ns? Pb, Cr, Cd OSHA Regulated? Yes
		SECTION VI – RI		
STABILITY: 🗹 S	TABLE	☐ UNSTABLE	COND	ITIONS TO AVOID: None known
		als to avoid): None		
			S: Noxio	us gas and odors including, methyl methacrylate,
		xide, hydrogen cyanide.		
HAZARDOUS POI			COND	ITIONS TO AVOID: Temperatures above 370° C
	SEC	CTION VII – SPILL O	R LEA	K PROCEDURES
				OR SPILLED: Careful clean up and return to
		Vacuum if possible. Avoi		
				e with Federal, State and Local regulations.
		ORTABLE QUANTITY (N.A.
		TE NO. (40 CFR 261.33)		
□ Theoretica		IPOUND (VOC) (as pack		
□ I neoretica	!	lbs. /gal.	Anaiyu	cal lbs. /gal.
SECTION VIII – SPECIAL PROTECTION INFORMATION				
RESPIRATORY PROTECTION (Specify Type): Provide adequate ventilation. NIOSH/MSHA approved respiratory protection as required.				
VENTILATION LOCAL EXHAUST (Specify Rate): Controlled w/hepa filter.				
MECHANICAL (General – Specify Rate):				
SPECIAL:				
OTHER:				
PROTECTIVE GLOVES (Specify Type): Normal				
OTHER PROTECT	ION EQL	JIPMENT: OSHA/NIOSH	l cartrido	ge filter.
SECTION IX – SPECIAL PRECAUTIONS				
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Contain in drums, vacuum is preferable in the event of spill.				
OTHER PRECAUTIONS:				

Prepared by:

Name (print): casey Williams
Title: Quality Assurance Manager
Date Reviewed: 02/19/2025