

FOUR WHEEL SERIES

AX4 SERIES • 115 VOLT

MODEL	213AX4	216AX4	311AX4
Capacity	2.0 GPM	2.0 GPM	3.0 GPM
Pressure	1300 PSI	1600 PSI	1100 PSI
Pump	Triplex, Oil Bath, Direct Drive	Triplex, Oil Bath, Belt Drive	Triplex, Oil Bath, Belt Drive
Motor/Voltage Fuse For	2.3 HP, 115 V, 1 PH, Fuse for 20 Amp.	2.3 HP, 115 V, 1 PH, Fuse for 20 Amp.	2.3 HP, 115 V, 1 PH, Fuse for 20 Amp.
Coil (Steel Pipe) Cold Water Wrap, Spiral Heating Section	95', Schedule 40	95', Schedule 40	95', Schedule 40
Burner, Pressure Atomizing, Auto Ignition, Fuel Consumption	Kero, or #1 Diesel, 175,000 BTU, 1.25 GPH	Kero, or #1 Diesel, 175,000 BTU, 1.25 GPH	Kero, or #1 Diesel, 175,000 BTU, 1.25 GPH
Fuel Tank	Plastic, 4.5 Gal.	Plastic, 4.5 Gal.	Plastic, 4.5 Gal.
Stack Size	8"	8"	8"
Temp. Control	Standard	Optional	Optional
Chemical	Low Pressure Injector	Precise Metered	Precise Metered
Float Tank	N/A	Plastic	Plastic
Steam Capacity (Optional)	N/A	N/A	N/A
Dimensions	L - 40" W - 27" H - 40"	L - 40" W - 27" H - 40"	L - 40" W - 27" H - 40"
Shipping Weight	400 lbs.	420 lbs.	420 lbs.



Optional: Available UL or CSA approved Optional: 126' coil

Xtreme models same specifications plus:

- Schedule 80 coil • Stainless steel wrapper (X4X Models)
- Fuel solenoid • High-limit temperature control



LOCAL: 605.934.2222	TOLL FREE: 800.255.6823	WEB: ALKOTA.COM	105 Broad Street Alcester, South Dakota 57001 USA
------------------------	----------------------------	--------------------	--