

NEW PRODUCT



Manufacturing Valvetrain For 80-Years & 2-Generations





£0±€£000

30-33012

Spring Only Kit & Valves



Manufactures	Honda®				
Years	1977-1978				
Models	CB 750 SOHC F2/3				

Spring Only Kit • High Performance										
KPMI P/N	Туре	Max Valve Lift		Installed Height		Seat Pressure	Open Pressure	@ Lift		
30-33000	Intake	.485"		1.460"		78#	248#	.485"		
	Exhaust									
Kit Includes		8	CrSi Valve Springs							
Retail				\$133.21						

- High performance spring only solution compatible with the OEM retainer and base
- Increased spring force and rates compared to the OEM springs designed for hi-lift cams and high RPM conditions
- Premium grade, super clean ground chrome silicon wire X-Rayed at regular intervals to check for inclusions, heat treated, and shot peened, insuring maximum spring life.

Valves • Black Diamond™ • Black Nitroneg Stems										
KPMI P/N	Туре	Head Diameter		Stem Diameter	Tulip	0. L.	Remarks			
30-33012	Intake	34.00mm	1.339"	0.2590"	20°	3.960"	Standard			
30-33016	Exhaust	31.00mm	1.220"	0.2585"	25°	3.935"	Standard			
				\$37.55						

- Material and workmanship for desired advantages
- One piece forged EV8-SS offers uninterrupted grain flow for head stability
- Tufftride® coated for a high durability, low friction impregnated surface finish
- "Super-Finished" stem allows for Formula 1 level coating consistency
- Highly controlled production tolerances for outstanding consistency
- Every surface is either CNC machined or ground as top quality valves should be
- Swirl polished or CNC machined profiles are Flow Bench tested for optimized air flow
- Street, Strip or Track. You are choosing extreme durability and performance

Contact a KPMI® Sales Representative Today! 650-557-2046, Ext. 802