

Safety data sheet

ACRYL 60

Revision date : 2009/06/24
Version: 1.0

Page: 1/5
(30337726/SDS_GEN_CA/EN)

1. Substance/preparation and company identification

Company
BASF CANADA
100 Milverton Drive
Mississauga, ON L5R 4H1

24 Hour Emergency Response Information
CANUTEC (reverse charges): (613) 996-6666
BASF HOTLINE (800) 454-COPE (2673)

Chemical family: acrylic polymers, aqueous solution

2. Hazardous ingredients

Not WHMIS controlled.

3. Hazard identification

Emergency overview

NO PARTICULAR HAZARDS KNOWN.

Potential health effects

Irritation:

The product has not been tested. The statement has been derived from the properties of the individual components.

4. First-aid measures

General advice:

First aid personnel should pay attention to their own safety. Remove contaminated clothing.

If inhaled:

If difficulties occur after vapour/aerosol has been inhaled, remove to fresh air and seek medical attention.

If on skin:

After contact with skin, wash immediately with plenty of water and soap. Under no circumstances should organic solvent be used. If irritation develops, seek medical attention.

If in eyes:

Flush with copious amounts of water for at least 15 minutes. If symptoms persist, seek medical advice.

If swallowed:

Rinse mouth and then drink plenty of water. Seek medical attention.

Safety data sheet

ACRYL 60

Revision date : 2009/06/24
Version: 1.0

Page: 2/5
(30337726/SDS_GEN_CA/EN)

5. Fire-fighting measures

Flash point: not applicable
Self-ignition temperature: not self-igniting

Suitable extinguishing media:
foam, water spray, dry extinguishing media, carbon dioxide

Unsuitable extinguishing media for safety reasons:
water jet

Hazards during fire-fighting:
carbon monoxide, carbon dioxide, harmful vapours, nitrogen oxides, fumes/smoke, carbon black

Protective equipment for fire-fighting:
Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Further information:
Sealed containers should be protected against heat as this results in pressure build-up. Keep containers cool by spraying with water if exposed to fire.

6. Accidental release measures

Personal precautions:
Use personal protective clothing. Do not breathe vapour/aerosol/spray mists. Sources of ignition should be kept well clear. Handle in accordance with good building materials hygiene and safety practice.

Environmental precautions:
Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

Cleanup:

For small amounts: Pick up with inert absorbent material (e.g. sand, earth etc.). Dispose of contaminated material as prescribed.
For large amounts: Pump off product.

7. Handling and storage

Handling

General advice:
Avoid aerosol formation. Avoid inhalation of mists/vapours. Avoid skin contact. No special measures necessary provided product is used correctly.

Protection against fire and explosion:
No special precautions necessary.

Storage

General advice:
Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame. Store protected against freezing. Protect from direct sunlight.

Temperature tolerance
Protect from temperatures below: 0 °C
Article R 234-9 and 10 (women): concerned

Safety data sheet

ACRYL 60

Revision date : 2009/06/24
Version: 1.0

Page: 3/5
(30337726/SDS_GEN_CA/EN)

8. Exposure controls and personal protection

Personal protective equipment

Respiratory protection:

Wear respiratory protection if ventilation is inadequate. Wear a NIOSH-certified (or equivalent) respirator as necessary.

Hand protection:

Chemical resistant protective gloves

Eye protection:

Safety glasses with side-shields.

Body protection:

Body protection must be chosen based on level of activity and exposure.

General safety and hygiene measures:

In order to prevent contamination while handling, closed working clothes and working gloves should be used. Handle in accordance with good building materials hygiene and safety practice. When using, do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. At the end of the shift the skin should be cleaned and skin-care agents applied. Gloves must be inspected regularly and prior to each use. Replace if necessary (e.g. pinhole leaks).

9. Physical and chemical properties

Form:	liquid	
Odour:	ammonia-like	
Odour threshold:	No data available.	
Colour:	white	
pH value:	9.5 - 10	(20 °C)
Boiling point:	100 °C	
Vapour pressure:	17 hPa	(20 °C)
Density:	1.03 g/cm ³	
Viscosity, dynamic:	30 mPa.s	(20 °C) No data available.
Solubility in water:		(20 °C) dispersible

10. Stability and reactivity

Conditions to avoid:

See MSDS section 7 - Handling and storage.

Substances to avoid:

strong acids, strong bases, strong oxidizing agents

Hazardous reactions:

The product is stable if stored and handled as prescribed/indicated.

Thermal decomposition:

No decomposition if stored and handled as prescribed/indicated.

Corrosion to metals:

No corrosive effect on metal.

Safety data sheet

ACRYL 60

Revision date : 2009/06/24
Version: 1.0

Page: 4/5
(30337726/SDS_GEN_CA/EN)

11. Toxicological information

Chronic toxicity

Other information:

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

The product has not been tested. The statements on toxicology have been derived from products of a similar structure and composition.

12. Ecological information

Environmental toxicity

Other ecotoxicological advice:

Ecological data are not available.

13. Disposal considerations

Waste disposal of substance:

Do not discharge into drains/surface waters/groundwater.

Dispose of in a licensed facility.

Container disposal:

Contaminated packaging should be emptied as far as possible; then it can be passed on for recycling after being thoroughly cleaned.

14. Transport information

Land transport

TDG

Not classified as a dangerous good under transport regulations

Sea transport

IMDG

Not classified as a dangerous good under transport regulations

Air transport

IATA/ICAO

Not classified as a dangerous good under transport regulations

15. Regulatory information

Federal Regulations

Safety data sheet

ACRYL 60

Revision date : 2009/06/24

Page: 5/5

Version: 1.0

(30337726/SDS_GEN_CA/EN)

Registration status:

DSL, CA

released / listed

Not WHMIS controlled.

THIS PRODUCT HAS BEEN CLASSIFIED IN ACCORDANCE WITH THE HAZARD CRITERIA OF THE CPR AND THE MSDS CONTAINS ALL THE INFORMATION REQUIRED BY THE CPR.

16. Other information

Local contact information

BASF Construction Chemicals

bcc_prps@basf.com

END OF DATA SHEET