



**Revision Number: 004.0** Issue date: 08/22/2011

# 1. PRODUCT AND COMPANY IDENTIFICATION

Loctite(R) 577 Thread Sealant Medium Product name: IDH number: 231119

Strength

Product type: Anaerobic Sealant 21456 Item number: Region: **United States** 

Company address: **Contact information:** Telephone: 860.571.5100 Henkel Corporation

One Henkel Way MEDICAL EMERGENCY Phone: Poison Control Center Rocky Hill, Connecticut 06067

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

## 2. HAZARDS IDENTIFICATION

**EMERGENCY OVERVIEW** 

HMIS: HEALTH: \*2 Physical state: Paste Yellow, dark FLAMMABILITY: 1 PHYSICAL HAZARD: Mild

**Personal Protection:** See MSDS Section 8

WARNING: MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION.

MAY CAUSE ALLERGIC SKIN REACTION.

Relevant routes of exposure: Eyes, Lungs, Skin

Potential Health Effects

Inhalation: May cause respiratory tract irritation.

Skin contact: May cause skin irritation. May cause allergic skin reaction.

Eye contact: May cause irritation.

Ingestion: Not expected to be harmful by ingestion.

Existing conditions aggravated by

exposure:

Color:

Odor:

Eye, skin, and respiratory disorders.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR

1910.1200).

See Section 11 for additional toxicological information.

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%	
Polyglycol dimethacrylate	25852-47-5	30 - 60	
Polyglycol dioctanoate	18268-70-7	10 - 30	
Lauryl methacrylate	142-90-5	5 - 10	
Vinyl acetal polymers, butyrals	63148-65-2	1 - 5	
Silica, amorphous, fumed, crystal-free	112945-52-5	1 - 5	
Tetradecyl methacrylate	2549-53-3	1 - 5	
Hexadecyl methacrylate	2495-27-4	1 - 5	
1-Acetyl-2-phenylhydrazine	114-83-0	0.1 - 1	

IDH number: 231119 Product name: Loctite(R) 577 Thread Sealant Medium Strength

# 4. FIRST AID MEASURES

**Inhalation:** Move to fresh air. If symptoms develop and persist, get medical attention.

Skin contact: If symptoms develop and persist, get medical attention. Wash with soap and

water. Remove contaminated clothing and footwear. Wash clothing before

reuse.

Eye contact: Flush with copious amounts of water, preferably, lukewarm water for at least

15 minutes, holding eyelids open all the time. Get medical attention.

**Ingestion:** Do not induce vomiting. Keep individual calm. Get medical attention.

#### 5. FIRE FIGHTING MEASURES

Flash point: > 100 °C (> 212°F) Pensky Martens closed cup

Autoignition temperature:

Flammable/Explosive limits - lower:

Not available.

Flammable/Explosive limits - upper:

Not available.

Extinguishing media: Foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear.

Unusual fire or explosion hazards: None

IDH number: 231119

Hazardous combustion products: Oxides of carbon. Oxides of nitrogen. Oxides of sulfur. Irritating organic

vapours.

## 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:** Do not allow product to enter sewer or waterways.

Clean-up methods: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder,

universal binder, sawdust). Store in a partly filled, closed container until

disposal.

## 7. HANDLING AND STORAGE

**Handling:** Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist.

Wash thoroughly after handling. Use only with adequate ventilation.

Storage: For safe storage, store at or below 38 °C (100.4 °F)

Keep in a cool, well ventilated area away from heat, sparks and open flame.

Keep container tightly closed until ready for use.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Polyglycol dimethacrylate	None	None	None	None
Polyglycol dioctanoate	None	None	None	None
Lauryl methacrylate	None	None	None	50 ppm
Vinyl acetal polymers, butyrals	None	None	None	None
Silica, amorphous, fumed, crystal-free	10 mg/m3 TWA Inhalable dust. 3 mg/m3 TWA Respirable fraction.	20 MPPCF TWA 0.8 mg/m3 TWA	None	None
Tetradecyl methacrylate	None	None	None	50 ppm TWA 75 ppm STEL
Hexadecyl methacrylate	None	None	None	None
1-Acetyl-2-phenylhydrazine	None	None	None	None

Engineering controls: No specific ventilation requirements noted, but forced ventilation may still be

required if concentrations exceed occupational exposure limits.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure

limit(s).

**Eye/face protection:** Safety goggles or safety glasses with side shields.

Skin protection: Neoprene gloves. Butyl rubber gloves. Natural rubber gloves. Use

impermeable gloves and protective clothing as necessary to prevent skin

contact.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:

Color:

Yellow, dark
Odor:

Mild
Odor threshold:

Paste
Yellow, dark
Mild
Not available.

pH:

3.0 - 6.0

Vapor pressure: < 5 mm hg (27 °C (80.6 °F))

Boiling point/range:

Melting point/ range:

Specific gravity:

Vapor density:

Not determined
Not available.

1.15 - 1.2
Not available.

Flash point: > 100 °C (> 212°F) Pensky Martens closed cup

Flammable/Explosive limits - lower:
Flammable/Explosive limits - upper:
Autoignition temperature:
Evaporation rate:
Solubility in water:
Partition coefficient (n-octanol/water):
VOC content:
Not available.
Slight
Not available.
VOC content:
0.1 %; 0.99 g/l

# 10. STABILITY AND REACTIVITY

Stability: Stable

Hazardous reactions: Will not occur.

Hazardous decomposition products: Oxides of carbon. Irritating organic vapours.

**Incompatible materials:** Peroxides.

IDH number: 231119

Conditions to avoid: See "Handling and Storage" (Section 7) and "Incompatibility" (Section 10).

## 11. TOXICOLOGICAL INFORMATION

Acute oral product toxicity: LD50 (rat) > 10,000 mg/kg (Estimated)

Acute dermal product toxicity: LD50 (rabbit) > 5,000 mg/kg

Product name: Loctite(R) 577 Thread Sealant Medium Strength

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Polyglycol dimethacrylate	No	No	No
Polyglycol dioctanoate	No	No	No
Lauryl methacrylate	No	No	No
Vinyl acetal polymers, butyrals	No	No	No
Silica, amorphous, fumed, crystal-free	No	No	No
Tetradecyl methacrylate	No	No	No
Hexadecyl methacrylate	No	No	No
1-Acetyl-2-phenylhydrazine	No	No	No

Hazardous components	Health Effects/Target Organs		
Polyglycol dimethacrylate	Irritant, Allergen		
Polyglycol dioctanoate	Irritant		
Lauryl methacrylate	Irritant, Allergen		
Vinyl acetal polymers, butyrals	Irritant		
Silica, amorphous, fumed, crystal-free	Nuisance dust		
Tetradecyl methacrylate	Irritant, Allergen		
Hexadecyl methacrylate	Irritant, Allergen		
1-Acetyl-2-phenylhydrazine	Allergen, Blood, Kidney, Mutagen, Some evidence of carcinogenicity		

## 12. ECOLOGICAL INFORMATION

**Ecological information:** Not available.

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: Not a RCRA hazardous waste.

# TRANSPORT INFORMATION

The shipping classification in this section are for bulk packaging only. Shipping classification may be different for non-bulk packaging as exceptions may apply. Refer to shipping documents for package specific transportation classification.

#### **U.S. Department of Transportation Ground (49 CFR)**

Proper shipping name: Environmentally hazardous substances, liquid, n.o.s.

Hazard class or division: Identification number: UN 3082 Packing group: Ш

**DOT Reportable quantity:** alpha,alpha-Dimethylbenzylhydroperoxide, Saccharin

#### International Air Transportation (ICAO/IATA)

Proper shipping name: Environmentally hazardous substance, liquid, n.o.s.

Hazard class or division: Identification number: UN 3082 Packing group: Ш

#### Water Transportation (IMO/IMDG)

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Hazard class or division: Identification number: UN 3082 Packing group: Ш

IDH number: 231119 Product name: Loctite(R) 577 Thread Sealant Medium Strength

# 15. REGULATORY INFORMATION

#### **United States Regulatory Information**

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12(b) Export Notification: None above reporting de minimus

CERCLA/SARA Section 302 EHS: None above reporting de minimus

Vinyl acetate (CAS# 108-05-4). Hydroquinone (CAS# 123-31-9).

CERCLA/SARA Section 311/312: Immediate Health, Delayed Health

CERCLA/SARA 313: None above reporting de minimus

California Proposition 65: This product contains a chemical known to the State of California to cause birth defects or

other reproductive harm. This product contains a chemical known in the State of California

to cause cancer.

#### **Canada Regulatory Information**

IDH number: 231119

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

WHMIS hazard class: D.2.B

#### 16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: 14, 15

Prepared by: Kyra Kozak Woods, Manager, Regulatory Affairs

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.