

# HDC Series

The HDC Series is the most affordable and efficient skid on the market today. This series is the best buy for a quick return on investment.



## Gasoline Belt Drive

- High quality fuel filter/water separator ensures clean fuel supply to the burner
- Stainless-steel coil wrap prevents rusting
- 12V burner (Battery not included)
- 1/2-inch schedule 80-coil with stainless-steel wrap heat exchanger
- On/Off burner switch
- Adjustable high pressure detergent injection
- Electric start engine
- 10-gallon polyethylene burner fuel tank
- 10-gallon polyethylene engine fuel tank



HDC-3505-0K6G  
(shown with optional adjustable  
temperature control, HX-0212)

### Additional Features:

#### Pump

- Belt drive triplex piston General or AR pump with ceramic plungers
- Factory preset unloader

#### Engine

- Performance-proven industrial gasoline engine with electric start (Battery not included)

#### Frame

- Heavy-duty powder coated steel tube frame

#### Components

- No. 1 or No. 2 diesel or kerosene fired burner (Not approved for bio-fuel)
- Pressure relief valve protects against excessive system pressure

#### Miscellaneous

- Temperature rise 150°F/66°C above ambient, maximum outlet temperature is 200°F

#### Unit Includes:

- Quick connect nozzles – 0°, 15°, 25°, 40° and adjustable soap nozzle
- 50-foot x 3/8-inch steel wire-braided pressure hose with quick connects
- Professional-grade insulated trigger gun with safety lock-off
- Adjustable pressure insulated dual lance
- Adjustable high pressure detergent injector

# HDC Series



Model Number	PSI	GPM	Displacement/Engine	Gas Tank Capacity	Burner Fuel Tank Capacity	Fuel Consumption	BTU per hour	Dimensions (LxWxH)	Ship Wt.	Net Wt.
HDC-3005-OK6G	3000	4.8	624cc Kohler	10.0 gallon	10.0 gallon	2.76 gph	386,400	50x34x46in.	844 lb.	725 lb.
HDC-3005-0V6G	3000	4.8	480cc Vanguard OHV	10.0 gallon	10.0 gallon	2.76 gph	386,400	50x34x46in.	844 lb.	725 lb.
HDC-3505-1H6G	3500	4.7	GX630 Honda OHV	10.0 gallon	10.0 gallon	2.76 gph	386,400	50x34x46in.	844 lb.	725 lb.
HDC-3505-OK6G*	3500	4.7	624cc Kohler	10.0 gallon	10.0 gallon	2.76 gph	386,400	50x34x46in.	844 lb.	725 lb.
HDC-4004-1H6A	4000	4.0	GX630 Honda OHV	10.0 gallon	10.0 gallon	2.45 gph	343,000	50x34x46in.	844 lb.	725 lb.

\*Higher performance 624cc Kohler engine.

Options:		
Part Number	Description	Fits Models
HX-0130	<b>Three-way ball valve</b> - Allows the pressure washer to be operated from garden hose, float tank or trailer supply by adjusting ball level valve	All models
HX-0147	<b>Four-point lifting capability</b> - Allows unit to be lifted by a crane	All models
HX-0156	<b>Hour meter</b> - Displays the number of hours unit has been in operation	All models
HX-0200	<b>Trapping unloader</b> - For longer hose runs and cleaning elevated areas	All models
HX-0212	<b>Adjustable temperature control</b> - Operator is able to adjust outlet water temperature between 96°F–250°F	All models
HX-0229	<b>Clutch drive option</b> - Stops the pump from spinning in bypass mode and helps to extend the life of the pump, changes GPM to 4.3 when added to the unit	3000 PSI models
HX-0230	<b>Clutch drive option</b> - Stops the pump from spinning in bypass mode and helps to extend the life of the pump, changes GPM to 4.2 when added to the unit	3500 PSI models

Accessories:		
Part Number	Description	Fits Models
AW-5740-0000	<b>Wheel kit</b> - Allows unit to become portable	All models
AW-6000-1006	<b>Hot water skid equipment cover</b> - Keeps your equipment clean, dry and looking like new, made from 600-denier vinyl-backed polyester, water resistant, drawstrings to secure cover, Mi-T-M logo	All models
AW-6000-1007	<b>Hot water skid equipment cover</b> - Keeps your equipment clean, dry and looking like new, made from 600-denier vinyl-backed polyester, water resistant, drawstrings to secure cover, no logo	All models
50-0170	<b>Stack adapter</b> - Allows 8-inch flue pipe to be installed to boiler exhaust port	All models
850-0324	<b>Gasket (For 50-0170)</b> - Seals between 50-0170 stack adapter and boiler housing	All models

POWERED by **HONDA**™

