



# ELEVATION

*Made in Colorado, for Colorado's Climate!*

## Elevation

### Premium 100% Acrylic Primers 1250 Block Filler

#### Description

*Elevation 100% Acrylic Block Filler* is a premium, 100% acrylic latex block filler that is formulated specifically to endure the rigors of Colorado's unique climate. It offers excellent filling properties and alkali resistance. May be used for interior and exterior applications, and can be top-coated with water-based or solvent-based top coats.

#### Application and Substrate Information

Mix or stir thoroughly before using. Block filler should be applied using brush, roller, trowel, or through airless spray equipment (2,000 psi, 0.028" tip or larger). A second coat may be applied at a minimum of 3-4 hours after applying the first coat as drying conditions allow.

For best results, temperatures (air, surface and material temperatures) should be at or above 40°F (4.4°C) and at least 5°F above the dew point before applying. These conditions must remain at or above these levels for at least 8 hours. Do not apply if condensation is expected within 4-6 hours of applying. A small amount of colorant (up to 4 oz. per gallon) may be added to approximate the color of the finish coat.

#### Old Western Paint Co., Inc.

2001 W. Barberry Pl.  
Denver, CO 80204  
Phone: 303-825-5147  
Fax: 303-825-2437  
www.oldwesternpaint.com

#### Product Data

Gloss/Sheen (60°)	< 10 units
VOC Content (g/L)	< 50
Viscosity (Krebs Units)	123 (± 3)
Density (lb/gal)	13.3
Weight Solids	57 %
Volume Solids	50 %
Coverage (1.5 dry film)	400 ft <sup>2</sup> *

\*Theoretical value; may vary based on substrate porosity/application method

#### Features and Benefits

- ✓ Designed specifically for Colorado's Climate
- ✓ Alkali resistant
- ✓ Excellent filling properties
- ✓ May be used under multiple top-coats
- ✓ Interior or exterior use

#### Thinning

Thinning is not required or recommended as it may adversely affect block-filling properties.

#### Dry Time

Will dry to touch in one hour or less; may be recoated after four hours. At least 24-hours of dry time is recommended prior to sanding. Typical time for full cure is 7 days. Dry time may be affected by poor ventilation, low temperatures, amount of colorant and/or high humidity areas.

#### Clean-up

Clean all tools and equipment with warm, soapy water.

#### Environmental/Health Considerations

Formulated without lead, mercury, and other heavy metals. Does not contain ethylene glycol. No reportable amount of crystalline silica.



# ELEVATION

*Made in Colorado, for Colorado's Climate!*

## Old Western Paint Co., Inc.

2001 W. Barberry Pl.  
Denver, CO 80204  
Phone: 303-825-5147  
Fax: 303-825-2437  
[www.oldwesternpaint.com](http://www.oldwesternpaint.com)

### General Surface Preparation

All foreign material, including loose or peeling paint, dirt, grease, oil, wax, chalk, mildew, rust, dust, curing agents, etc., must be removed prior to use. Failing to do so may compromise proper adhesion and overall performance. Caulk all cracks and open seams. Putty all nail holes. An appropriate primer should be used when coating highly porous substrates. A stain blocking primer, such as *Elevation All-Prime*, is recommended over areas where stains can 'bleed through' to the surface. Glossy surfaces should be dulled prior to coating, and rough or patched surfaces should be sanded.

### Specific Substrate Recommendations

**Siding:** Not recommended for traditional siding unless surface is highly porous.

**Concrete/Masonry Block:** New concrete block and masonry should cure for at least 30 days prior to priming. The surface pH should be below 10.5. Not recommended for smooth concrete.

**Metal:** Not recommended.

**Drywall/Gypsum Board:** Not recommended.

**Wood:** Not recommended.

### Packaging

Available in 5-gallon containers.

### Intended Use

To be used in a manner consistent with latex wall paints and finishes. Do not take internally. Keep out of reach of children and pets. Not recommended for floors or where water can puddle. Keep from freezing.

**WARNING:** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC AND MAY CAUSE SERIOUS ILLNESS IF YOU ARE EXPOSED, ESPECIALLY FOR CHILDREN OR THOSE WHO ARE PREGNANT. Wear a properly fitted NIOSH-approved respirator and prevent skin contact to minimize lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. For further information, contact the U.S.E.P.A. National Lead Information Hotline at 1-800-424-LEAD or visit [www.epa.gov/lead](http://www.epa.gov/lead).

### Disclaimer

All information and data appearing in this document are provided in good faith and are believed to be reliable and accurate to the best of our knowledge at the date of publication. None of the provided information is to be considered a warranty or quality specification or all-inclusive and is given only as a guidance. It is the user's responsibility to determine the intended utilization of the product. No guarantee, expressed or implied, is made by Old Western Paint Co., Inc. And the user assumes all risk and responsibility.