Natural Daylight Solutions Ltd

Integrated Natural Ventilation & Daylight Solutions

NDS DayTube / DayFlex

The NDS DayTube rooflights are designed for fast, hassle free installation and maximum light transmission. The polycarbonate dome sits on a roof plate to collect the maximum amount of daylight possible and it is reflected to the interior below through a rigid aluminium tube. Single skin polycarbonate dome with double sided UV protection provides 90% light transmission.

	Options available:		
(Helling)	The second state of the second		
Sizes:	3 diameters to maximise light transmission (12"/305mm, 14"/355m	m, 21"/535mm)	
Roof plate:	Plain tile, Profiled tile and Plate options	the formation	
Roof kits:	Pitched and flat	STAR NET	
Glazing Colour:	Clear, Textured, Opal	the second second	
Glazing Skin:	Single glazed		-
Configuration:	Fixed unit or Fixed with Kerb	C. S. P. S. L.	
Kerb:	PVC Kerb	190	A State
Ventilation:	Non-opening only		
Light Transmission	.90%		
Total Reflection:	DIN 5036-3 95%		
Diffuse Reflection:	DIN 5036-3 <12%		
Brightness – along:	ISO 7688 89%		
Brightness – across	: ISO 7688 88%		•
Image Clarity:	ASTM E-430 95%		
	 Plain Tile Profielt Ref State - a situatization Bat Roof Plain Tile Profielt Ref Profielt Ref Profielt Ref Plain Tile Profielt Ref Prof		1
DayTube	· · · · · · · · · · · · · · · · · · ·	DayFlex	

Please call $0333\ 772\ 0609$ for further details

www.naturaldaylightsolutions.com