

9 SERIES EASY READ-MAGSTRIPE™ CARD READER



- Stainless steel read head
- Includes starter pack with master card and 100 enrollment (shadow) cards used to enroll and delete users
- Programming of opening time and lock mode is set with master card
- Can program up to a maximum of 1,000 cards per reader
- Satin chrome finish
- Accepts any ANSI standard Track II magstripe® card such as a drivers license or credit card
- For internal or external use (-20°C)
- Size: 1-3/8"W x 3-1/2"H x 1-3/8"D

MFG #	DESCRIPTION	EZ #
9310MRK6 26D	Reader With Starter Pack	070929
931 250SC	Package Of 100 Shadow Cards	070930

9 SERIES STANDALONE DIGITAL KEYPADS



9212I

9212I/ 9212ILW

- Keypad programmable
- Single gang flush mount design
- 120 user capability
- Electronics mounted on back of keypad
- Stainless steel faceplate
- Three LED's to indicate status and provide user with visual PIN entry confirmation
- Field selectable 12-24 VAC/VDC

9212I - INTERIOR USE

- Input trigger for Request-To-Exit (REX) or other open circuit contact
- Up to 4 independant outputs assignable by code
- All outputs programmable for latched or timed operation
- Size: 2-3/4" x 4-1/2" x 1-1/4"

9212ILW - INTERIOR OR EXTERIOR USE

- Heavy chrome plated trim ring
- Key press feedback via sounder and yellow LED
- Built-in assignable sounder
- Bi-color Red/Green LED indicates relay status
- Size: 3-3/8" x 5-1/8" x 5/8"



9212ILW

9235I - INTERIOR USE

- Accommodates up to 120 users
- EEPROM memory ensures programming remains intact when unit is not powered
- Secure access codes (4-8 digits)
- Silent mode (audible annunciation of key presses can be disabled)
- Programmable lockout
- Variable output time delay (1-60 seconds)
- Interior and exterior models
- Surface mount design
- 12 VDC
- Size: 2-3/4" x 4-1/2" x 1-5/32"



9325I

MFG #	RELAY RATING	INPUT VOLTAGE	BACKLIT	EZ #
9212I	8A@250V	12-24 VAC/VDC	No	100313
9212ILW	2A@30VAC/DC	12-24 VAC/VDC	Yes	101780
9325I	5A@30V	12VDC	Yes	080344